

SWT-P-242-360

24 Port PoE Switch



Key Features

- Conforms to IEEE802.3, IEEE802.3u, IEEE802.3af
- Provides (24) 10/100Base-TX ports and (2) combo ports (10/100/1000Base-T or 1000Base-X)
- High back-plane bandwidth 5Gbps
- IEEE802.3x Flow control
- Plug and play operation
- Surge protection for power port and data ports
- EMI standards complies with FCC, CE class B
- 2 Year Warranty

SWT-P-242-360

Fixed Port	(24) 10/100Base-TX ports (2) Combo ports (10/100/1000Base-T or 1000Base-X) (2) Shared SFP ports
LED Indicators	PWR, PoE, Link/Act VLAN LED
Thermal Methods	Built-in Noiseless Fan
Switching Capacity	8.8 G.
MAC Address Table	8K
Traffic Control	IEEE 802.3x full-duplex flow control
PoE	
PoE Port	(24) 10/100Base-TX ports
PoE Standard	IEEE802.3af, per port 15.4W
ENVIRONMENTAL	
Operating Temperature	0°C~45°C - 32°F~113°F
Storage Temperature	-10°C~70°C - 14°F~158°F
Operating Humidity	10%~90% (non-condensing)
ELECTRICAL	
Input Voltage	100V~240V AC, 50/60Hz
Power Consumption	370W
MECHANICAL	
Dimensions (WxHxD)	13.5" x 1.65" x 7.2"
Weight	7.6 lbs

* Design and specifications are subject to change without notice.