

DT Series

Mini Desktop Control Consoles



The **SDC mini desktop consoles** provide an economical method of controlling one or two doors. They are available in four switch configurations with tri-color LED indicators. When used with a door status or lock status sensor the LED's allow monitoring of door and lock modes. The switches can provide an on/off function or momentary access control for electromagnetic EMLocks, shear locks, bolt locks, delayed egress systems, electrical exit system, or electric strikes.

A choice of heavy duty momentary or alternate action operating switches accommodate lock control functions. The momentary switch can be used to release a single opening. The alternate action on/off switch is used as a bypass for keeping the door unlocked for an extended period of time.

The tri-color LED displays green, red and amber colors to indicate up to three lock status conditions for immediate status indication of door position or lock status when used with lock monitors such as door position (DPS) or bond sensors (BAS).

MODELS

- DTMO-1** One Momentary (MO)
- DTMA-1** One Alternate Action (On/Off)
- DTMO-2** Two Momentary (MO)
- DTMA-2** Two Alternate Action (On/Off)
- DTMOMA-2** One Momentary (MO), One Alternate Action (On/Off)

STANDARD FEATURES

- Reliable push buttons for switch activation
- Accommodates lock control functions
- Visual status indicator (LED)



**DTMO-1
DTMA-1**



**DTMO-2
DTMA-2
DTMOMA-2**



SPECIFICATIONS

	DT
Contact	SPDT 5 Amp @ 30 VDC Resistive
LED Power (Max)	30 mA @ 24 VDC
Color	Biege
Dimensions	4 1/8" x 3 1/8" x 6 1/4"

HOW TO ORDER

FOLLOW STEPS FOR ORDERING

 Designates optional step

1| SPECIFY MODEL

DTMO-1 One Momentary (MO) Switches

DTMO-2 Two Momentary (MO) Switches

DTMOMA-2 One Momentary (MO) Switch, One Alternate Action (On/Off) Switch

DTMA-2 Two Alternate Action (On/Off) Switches

STEP NUMBER: 1

ORDERING EXAMPLE: **DTMO-2**