

Complete Component Considerations™

1 Locking Device

- Electric Strike
- Delayed Egress Lock
- Electric Bolt Lock
- Electrified Lockset
- Exit Device
- Frame Actuator Lockset
- Magnetic Lock



Spacesaver® 1091A



Selectric Pro™ Z7800



EMLock® 1511
1650 lbs



Exit Check™ 1511S
Delayed Egress Lock



UniFLEX™ 55



Electra Pro™ Z7200



HiShear® 1565 - 2700 lbs



Spectra® 6000

- Dual Latch Retraction & Dogging
- Delayed Egress
- Exit Alarm
- Electric Mortise
- HiTower® Actuator



2 Access Control

- Standalone or Network
- Keyswitch
- Digital Keypad
- Card Reader



Entry Check™
920PW



IP Pro
IP-based Access Control



Entry Check™ 918



EntryCheck™ 924P



704U Keyswitch

3 Egress Device

- Exit Switch
- PIR Egress Sensor
- Exit Sense Bar
- Emergency Door Release



422U



463U



474U



482A6U



Egress PIR MD31D



Sure Exit® PSB560



492 Emergency
Door Release

4 Hold & Release Control

- Magnetic Door Holder Release Device



EH20



EH40

5 Power Transfer Devices

Required With Locksets & Exit Devices


- Electric Power Hinge
- Power Transfer Loop
- Concealed Power Transfer



PTM-2
PTM-10



PTH-4
PTH-10



PT-2U

6 Power Supply & Door Controller

- 12/24VDC, Class 2
- Fire release input
- System Status LED's
- Multiple Fused Outputs
- Multiple Relay Configurations
- Universal Programmable Controllers



- 602RF 1 Amp
- 631RF 1.5 Amp
- 632RF 2 Amp
- 634RF 4 Amp
- 636RF 6 Amp



FB-4: 4 Fused
Outputs




CR-4: 4 Fused
Relay Outputs



UR-2-4 & UR-4-8:
7 Selectable Systems
7 Selectable Relay Modes

7 Annunciators



EA100



101-4AM



101-1A

1511 EMLock® (1650 lb.) and TJ1V

Optional TJ Bracket
Optional HDB Glass Bracket

1571V EMLock® 1200lb Energy Saver Single

1572V EMLock® 1200lb Energy Saver Double

1581 EMLock® (650 lb.)

1581 EMLock® (650 lb.) & TJ81V

1583 Cabinet EMLock® (300 lb.)

1511S Exit Check® Delayed Egress Lock with Voice Notification

PUSH UNTIL ALARM SOUNDS. DOOR CAN BE OPENED IN 15 SECONDS

1581S 650 lb Mini Exit Check®

1565 Hi/Shear® Lock (2700 lb.)

Electric Strikes

15 30-4 45 55

E70 Series Standalone Electronic Lockset

STANDALONE Keypad BLUETOOTH Software STANDALONE Proximity

7500 HiTower® Wiring in Frame Only

7200 Electra Pro™

7800 SELECTRIC® Wiring Through Door

Bolt Locks

FS23M Dual Fail Safe

1091A Fail Safe
1291A Fail Secure

160 Fail Safe
260 Fail Secure

2090A Fail Secure

180A Fail Safe
280 Fail Secure

Momentary Key & Push Switches

463U 432UL2 492

452UL2 702NUL2 702UL2

Power Supplies

602RF 1.0 amp 631RFA 1.5 amp
631RF 1.5 amp 632RFA 2.0 amp
632RF 2.0 amp 634RF 4.0 amp
636RF 6.0 amp

Field Selectable 12/24VDC

EntryCheck® Access Control Keypads

918 500 Users 920/920P 500 Users 923/923P 500 Users