



SF301A, SF302 Call Cords IL338 Specification Sheet

Tek-CARE® Nurse Call Systems • Rev. 18 - 06/2013

Features

- UL® 1069 Listed
- Oxygen safe
- Impact resistant and waterproof
- Small, lightweight pendant fits comfortably in hand
- Bed clips included

Description

The TekTone® SF301A (single) or SF302 (double) call cords are for use with the Tek-CARE® NC110N, NC150N, NC200N and NC300™II Nurse Call Systems, and the Tek-CARE®500 Wireless Emergency Call System, where ¼" phono jacks are used. Ten-foot cords are also available as SF301A/10 and SF302/10. The SF301A and SF302 are oxygen safe call cords certified safe for use by all patients receiving oxygen therapy. These waterproof and impact resistant call cords have completely sealed push buttons.



SF301A, SF302 Call Cords

Listings



UL® 1069 Listed; UL® File Number E71599.

Specifications

Connection: ¼" (6.35 mm) plug-in phono jack
 Construction: SPST-1A switch
 Integral brass, fine silver contacts
 1 AMP, 115 watt maximum, AC
 Dimensions: 7' (2.13 m) long polyvinyl covered cord

Required Components

Tek-CARE®500 Wireless Emergency Call System
with SF530 Room Station

or

Tek-CARE® NC300™II Nurse Call System
with SF380A Patient Stations

or

Tek-CARE® NC200N or NC150N Nurse Call Systems
with IR151B or IR152B Patient Stations

or

Tek-CARE® NC110N Nurse Call System
with SF100C or SF102 Patient Stations

www.tektone.com

277 Industrial Park Road • Franklin, NC 28734 • tektone@tektone.net

Phone: (828) 524-9967 • Fax: (828) 524-9968 • Sales: Choose option 2 • Tech Support: Choose option 3

TekTone®'s quality system is registered by UL® to the ISO 9001 standard. (Reference #10001510.)