

#### Tek-CARE400 P5/P5+ and Tek-CARE300III Nurse Call Systems • Rev. 8 - 10/2019

### **Features**

- UL<sup>®</sup> 1069 Listed
- Oxygen safe
- Impact resistant and waterproof
- Small, lightweight pendant fits comfortably in hand
- · Bed clips included

### Description

The TekTone SF401A single call cord is for use with the Tek-CARE400, Tek-CARE400 P5/P5+, and Tek-CARE300III Nurse Call Systems, where 8-pin DIN jacks are used. The SF401A is an oxygen safe call cord that is certified safe for use by all patients receiving oxygen therapy. This waterproof and impact resistant call cord has a completely sealed push button and a polyvinyl-covered cord.

# **Specifications**

Dimensions:	SF401A:	7' (2.13 m) long
	SF401A/10:	10' (3.05 m) long
	SF401A/15:	15' (4.57 m) long
	SF401A/20:	20' (6.10 m) long
Connection:	8-pin DIN plug	
Construction:	SPST1-A switch Integral brass, fine silver contacts 1 AMP, 15 watt maximum, AC	

# Listings



UL<sup>®</sup> 1069 Listed and cUL<sup>®</sup> Listed to CSA C22.2 No. 205; UL<sup>®</sup> File Number E71599.



SF401A Oxygen-Safe Call Cord

### **Required Components**

for the Tek-CARE400 Nurse Call System: IR411, IR412, IR412EPB patient stations

for the Tek-CARE400 P5/P5+ Nurse Call System: IR411P5/IR421P5, IR412P5/IR422P5 patient stations

for the Tek-CARE300III Nurse Call System: IR319B, IR320B patient stations

324 Industrial Park Road • Franklin, NC 28734 • tektone@tektone.net Phone: 828.524.9967 • Fax: 828.524.9968 • Sales: Choose option 2 • Tech Support: Choose option 3 TekTone's quality system is registered by DQS to the ISO 9001:2015 standard.