

# LBB 1949/00 Gooseneck Condenser Microphone

www.boschsecurity.com



**BOSCH**  
Invented for life



- ▶ Unidirectional condenser microphone
- ▶ Flexible stem
- ▶ Phantom powered by amplifier
- ▶ On/off sliding switch with priority contact
- ▶ Supplied with fixed 2 m (78 in) cable and lockable DIN connector

The gooseneck microphone is a stylish high quality unidirectional condenser microphone, mainly intended for public address applications.

## Functions

The flexible stem base has a screw fitting, and the microphone comes with a multi-thread adaptor (3/8", 1/2", and 5/8") for mounting onto floor-stands, lecterns, panels or desktops. The microphone runs off the phantom power supply from the amplifier to which it is connected.

The on-off sliding switch, not only switches on the microphone, but also provides priority contacts for remote control switching purposes. If the priority contacts are not required, the microphone can be connected to amplifiers with 3-pin XLR-inputs, using the DIN to XLR adapter.

## Certifications and approvals

Immunity	acc. to EN 55103-2
Emission	acc. to EN 55103-1

Region	Certification
Europe	CE

## Parts included

Quantity	Component
1	LBB 1949/00 Gooseneck Condenser Microphone
1	DIN to XLR adapter

## Technical specifications

### Electrical\*

Phantom power supply	
Voltage range	12 to 48 V
Current consumption	<8 mA
Performance*	
Sensitivity	0.7 mV @ 85 dB SPL (2 mV/Pa)
Maximum input sound level	110 dB SPL

Distortion	<0.6% (maximum input)
Equivalent input noise level	28 dBA SPL (S/N 66 dBA ref. 1 Pa)
Frequency response	100 Hz to 16 kHz
Output Impedance	< 200 ohm

\* Technical performance data acc. to IEC 60268-4

### Mechanical

Dimensions (D x L)	30 x 500 mm (19.69 x 1.18 in)
Weight	Approx. 300 g (10.5 oz)
Color	Dark gray
Cable length	2 m (78 in)
Connector	5-pin DIN 180° (lockable)

### Environmental

Operating temperature	-10 °C to +55 °C (+14 °F to +131 °F)
Storage temperature	-40 °C to +70 °C (-40 °F to +158 °F)
Relative humidity	<95%

### Ordering information

#### LBB 1949/00 Gooseneck Condenser Microphone

Condenser gooseneck microphone, unidirectional, non-reflective dark gray finish, flexible stem, On/off switch with priority contact, fixed 2 m (78 in) cable with 5 pin DIN 180 degrees (lockable) connector. DIN to XLR adapter standard supplied.

Order number **LBB1949/00**

#### Accessories

##### LBC 1102/02 Cable Transformer

for galvanic separation

Order number **LBC1102/02**

##### LBC 1208/40 Microphone Cable

Microphone connection/extension cable, 3-pin XLR, 10 m (32.8 ft).

Order number **LBC1208/40**

#### Represented by:

##### Americas:

Bosch Security Systems, Inc.  
12000 Portland Avenue South  
Burnsville MN 55337, USA  
Phone: +1-800-392-3497  
Fax: +1-800-955-6831  
audiosupport@us.bosch.com  
www.boschsecurity.com

##### Europe, Middle East, Africa:

Bosch Security Systems B.V.  
P.O. Box 80002  
5617 BA Eindhoven, The Netherlands  
Phone: + 31 40 2577 284  
Fax: +31 40 2577 330  
emea.securitysystems@bosch.com  
www.boschsecurity.com

##### Asia-Pacific:

Robert Bosch (SEA) Pte Ltd, Security Systems  
11 Bishan Street 21  
Singapore 573943  
Phone: +65 6571 2808  
Fax: +65 6571 2699  
apr.securitysystems@bosch.com  
www.boschsecurity.asia

##### China:

Bosch (Shanghai) Security Systems Ltd.  
201 Building, No. 333 Fuquan Road  
North IBP  
Changning District, Shanghai  
200335 China  
Phone +86 21 22181111  
Fax: +86 21 22182398  
www.boschsecurity.com.cn

##### America Latina:

Robert Bosch Ltda Security Systems Division  
Via Anhanguera, Km 98  
CEP 13065-900  
Campinas, Sao Paulo, Brazil  
Phone: +55 19 2103 2860  
Fax: +55 19 2103 2862  
latam.boschsecurity@bosch.com  
www.boschsecurity.com