

OVERVIEW

Basic rPDUs deliver reliable power to critical IT equipment within a rack or cabinet.

Benefits

- Reliable rack power distribution.
- Every unit is 100% tested for reliability and functionality.
- Simple and convenient configuration options for cord lengths and chassis colors.
- Standard three-year warranty, upgraded to a five-year warranty with product registration.





Part #: VP9562

Model Number: BRN100-10

Category: Basic

Sub Category: Standard

Power Configuration: 15A, 120V, 1.4kW

Physical Configuration: 19in / 483mm, Horizontal

Product Summary:

rPDU, Basic Standard, 15A, 120V, 1.4kW, Horizontal, (10) NEMA 5-15R, 10ft power cord

with 5-15P, Black Powder Coat.

Plug Form: Receptacle:







NEMA 5-15R (Quantity: 10)

Chassis Color Options:



To discuss color options, contact your local sales representative.

Product Specification and Options

System Features

Quantity Of Inputs	1
Voltage	100-120V
Current	15A
VA per Input (Load Capacity)	1.4kW (120V)
Frequency	50/60Hz

Indicators - LED(s) 1 - Power ON Green LED Power Cable Wire Gauge 14/3 Power Cable Length 10ft Plug Type NEMA 5-15P Receptacle/Socket Type #1 NEMA 5-15R - Quantity on Rear 10 - Quantity per Breaker 10 - Style Duplex - Maximum Output per Receptacle/Socket 15A - Voltage per Receptacle/Socket 120V Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 19in / 483mm Horizontal Rackmount Flush Mount Yes Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years Certification/Agency Approvals Chassis Dimensions (HxWxD) 1.72in x 17in x 3.75in		
Indicators - LED(s) 1 - Power ON Green LED Power Cable Wire Gauge 14/3 Power Cable Length 10ft Plug Type NEMA 5-15P Receptacle/Socket Type #1 NEMA 5-15R - Quantity on Rear 10 - Quantity per Breaker 10 - Style Duplex - Maximum Output per Receptacle/Socket 15A - Voltage per Receptacle/Socket 120V Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 19in / 483mm Horizontal Rackmount Flush Mount Yes Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years Certification/Agency Approvals Chassis Dimensions (HxWxD) 1.72in x 17in x 3.75in	Over Current Protection	15A Thermal Breaker
Power Cable Wire Gauge 14/3 Power Cable Length 10ft Plug Type NEMA 5-15P Receptacle/Socket Type #1 NEMA 5-15R - Quantity on Rear 10 - Quantity per Breaker 10 - Style Duplex - Maximum Output per Receptacle/Socket 15A - Voltage per Receptacle/Socket 120V Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 19in / 483mm Horizontal Rackmount Flush Mount Yes Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years Certification/Agency Approvals Chassis Dimensions (HxWxD) 1.72in x 17in x 3.75in	Switch	No
Power Cable Length 10ft Plug Type NEMA 5-15P Receptacle/Socket Type #1 NEMA 5-15R - Quantity on Rear 10 - Quantity per Breaker 10 - Style Duplex - Maximum Output per Receptacle/Socket 15A - Voltage per Receptacle/Socket 120V Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 19in / 483mm Horizontal Rackmount Flush Mount Yes Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years Certification/Agency Approvals Chassis Dimensions (HxWxD) 1.72in x 17in x 3.75in	Indicators - LED(s)	1 - Power ON Green LED
Plug Type NEMA 5-15P Receptacle/Socket Type #1 NEMA 5-15R - Quantity on Rear 10 - Quantity per Breaker 10 - Style Duplex - Maximum Output per Receptacle/Socket 15A - Voltage per Receptacle/Socket 120V Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 19in / 483mm Horizontal Rackmount Flush Mount Yes Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years Certification/Agency Approvals Chassis Dimensions (HxWxD) 1.72in x 17in x 3.75in	Power Cable Wire Gauge	14/3
Receptacle/Socket Type #1 Quantity on Rear Quantity per Breaker 10 Style Duplex Maximum Output per Receptacle/Socket 15A Voltage per Receptacle/Socket 120V Continuous Operating Temperature Range Heavy Steel - Powder Coat Finish Black Configuration 19in / 483mm Horizontal Rackmount Flush Mount Yes Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty S-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years Certification/Agency Approvals Chassis Dimensions (HxWxD) 1.72in x 17in x 3.75in	Power Cable Length	10ft
- Quantity on Rear 10 - Quantity per Breaker 10 - Style Duplex - Maximum Output per Receptacle/Socket 15A - Voltage per Receptacle/Socket 120V Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 19in / 483mm Horizontal Rackmount Flush Mount Yes Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years Certification/Agency Approvals RoHS Compliant Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (HxWxD) 1.72in x 17in x 3.75in	Plug Type	NEMA 5-15P
- Quantity per Breaker - Style - Duplex - Maximum Output per Receptacle/Socket - Voltage per Receptacle/Socket - Voltage per Receptacle/Socket - Voltage per Receptacle/Socket - 120V Continuous Operating Temperature Range - 10-45C / 50-113F Heavy Steel - Powder Coat Finish - Black Configuration - 19in / 483mm Horizontal Rackmount Flush Mount - Yes Country of Origin - USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty - S-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years Certification/Agency Approvals - Certification/Agency Approvals - UL & c-UL Listed 60950 Chassis Dimensions (HxWxD) - 1.72in x 17in x 3.75in	Receptacle/Socket Type #1	NEMA 5-15R
Duplex - Maximum Output per Receptacle/Socket - Voltage per Receptacle/Socket 120V Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 19in / 483mm Horizontal Rackmount Flush Mount Yes Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years Certification/Agency Approvals Certification/Agency Approvals Chassis Dimensions (HxWxD) 1.72in x 17in x 3.75in	- Quantity on Rear	10
- Maximum Output per Receptacle/Socket 15A - Voltage per Receptacle/Socket 120V Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 19in / 483mm Horizontal Rackmount Flush Mount Yes Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years Certification/Agency Approvals RoHS Compliant Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (HxWxD) 1.72in x 17in x 3.75in	- Quantity per Breaker	10
- Voltage per Receptacle/Socket Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 19in / 483mm Horizontal Rackmount Flush Mount Yes Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years Certification/Agency Approvals RoHS Compliant Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (HxWxD) 1.72in x 17in x 3.75in	- Style	Duplex
Continuous Operating Temperature Range 10-45C / 50-113F Heavy Steel - Powder Coat Finish Black Configuration 19in / 483mm Horizontal Rackmount Yes Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years Certification/Agency Approvals RoHS Compliant Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (HxWxD) 1.72in x 17in x 3.75in	- Maximum Output per Receptacle/Socket	15A
Heavy Steel - Powder Coat Finish Black Configuration 19in / 483mm Horizontal Rackmount Yes Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years Certification/Agency Approvals Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (HxWxD) 1.72in x 17in x 3.75in	- Voltage per Receptacle/Socket	120V
Configuration 19in / 483mm Horizontal Rackmount Yes Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years Certification/Agency Approvals Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (HxWxD) 1.72in x 17in x 3.75in	Continuous Operating Temperature Range	10-45C / 50-113F
Flush Mount Yes Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant Product Warranty 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years Certification/Agency Approvals RoHS Compliant Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (HxWxD) 1.72in x 17in x 3.75in	Heavy Steel - Powder Coat Finish	Black
Country of Origin USA, TAA Compliant and Buy American Act COTS Compliant 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years Certification/Agency Approvals Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (HxWxD) 1.72in x 17in x 3.75in	Configuration	19in / 483mm Horizontal Rackmount
Product Warranty 5-year limited warranty if registered within 120 days of purchase, otherwise warranty defaults to 3 years Certification/Agency Approvals Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (HxWxD) 1.72in x 17in x 3.75in	Flush Mount	Yes
purchase, otherwise warranty defaults to 3 years Certification/Agency Approvals Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (HxWxD) 1.72in x 17in x 3.75in	Country of Origin	USA, TAA Compliant and Buy American Act COTS Compliant
Certification/Agency Approvals UL & c-UL Listed 60950 Chassis Dimensions (HxWxD) 1.72in x 17in x 3.75in	Product Warranty	
Chassis Dimensions (HxWxD) 1.72in x 17in x 3.75in	Certification/Agency Approvals	RoHS Compliant
	Certification/Agency Approvals	UL & c-UL Listed 60950
Shipped Weight 6lbs (2.72kg)	Chassis Dimensions (HxWxD)	1.72in x 17in x 3.75in
	Shipped Weight	6lbs (2.72kg)