

PRO SERIES

4MP WDR IR Bullet Camera




MPIX-40BIMR



Features:

- ❖ Motorized IR bullet camera
- ❖ 1/3" 4MP progressive scan CMOS
- ❖ 25/30fps@4Mp(2688×1520)
- ❖ H.265 & H.264 triple-stream encoding
- ❖ WDR up to 120dB
- ❖ Day/Night(ICR), 3DNR, Auto Iris, AWB, AGC, BLC
- ❖ 2.7mm - 13.5mm motorized lens
- ❖ Max. IR LEDs length 50m/164feet
- ❖ 2/1 Alarm in/out, 1/1 audio in/out
- ❖ Micro SD memory, IP67, PoE
- ❖ Multiple network monitoring:
Built-in web server & Multifunction VMS
- ❖ Smart phones compatible
- ❖ Supports multiple analytic functions.
For more Information call us to better suit your needs.




FREE Multisite VMS Software
Download from www.watchnetinc.com



Optional Bracket:



BRACK-BB-53
Wall Mount Bracket included



iPhone



Model	MPIX-40BIMR
Camera	
Image Sensor	1/3" 4Megapixel progressive scan CMOS
Effective Pixels	2688(H) x 1520(V)
Min. Illumination	0.03Lux/F1.4 (Color,1/3s,30IRE) 0.3Lux/F1.4 (Color,1/30s,30IRE) 0Lux/F1.4(IR on)
RAM / ROM	512MB / 32MB
S/N Ratio	More than 50dB
Scanning System	Progressive
Electronic Shutter Speed	Auto/Manual, 1/3~1/100000s
IR Distance	Distance up to 50m (164ft)
IR LEDs	4
IR On / Off Control	Auto / Manual
Lens	
Lens Type	Motorized / Auto Iris (DC)
Focal Length	2.7mm - 13.5mm motorized lens
Max. Aperture	F1.4
Angle of View	H: 106°~31°, V:58°~17°
Mount Type	Board-in Type
Optical Zoom	5x
Close Focus Distance	0.3m
Focus Control	Motorized
Video	
Compression	H.265+/H.265/H.264+/H.264
Streaming Capability	3 Streams
Resolution	4M(2688×1520)/3M(2304×1296)/ 1080P(1920×1080)/1.3M(1280×960)/ 720P(1280×720)/D1(704×576/704×480)/ VGA(640×480)/CIF(352×288/352×240)
Frame Rate	Main Stream: 4M(1~25/30fps) Sub Stream: D1(1~25/30fps) Third Stream: 720P(1~25/30fps)
Bit Rate Control	CBR/VBR
Bit Rate	H.264: 24 ~ 10240Kbps H.265: 14 ~ 9984Kbps
Day/Night	Auto(ICR) / Color / B/W
BLC Mode	BLC / HLC / WDR(120dB)
White Balance	Auto/Natural/Street Lamp/Outdoor/Manual
Gain Control	Auto/Manual
Noise Reduction	3D DNR
Motion Detection	Off / On (4 Zone, Rectangle)
Region of Interest	Off / On (4 Zone)
Electronic Image Stabilization (EIS)	N/A

Smart IR	Support
Defog	N/A
Digital Zoom	16x
Flip	0°/90°/180°/270°
Mirror	Off / On
Privacy Masking	Off / On (4 Area, Rectangle)
Audio	
Compression	G.711a / G.711Mu / AAC / G.726
Network	
Ethernet	RJ-45 (10/100Base-T)
Protocol	HTTP; HTTPS; TCP; ARP; RTSP; RTP; UDP; SMTP; FTP; DHCP; DNS; DDNS; PPPOE; IPv4/v6; QoS; UPnP;NTP; Bonjour; 802.1x; Multicast; ICMP; IGMP; SNMP
Interoperability	ONVIF, PSIA, CGI
Streaming Method	Unicast / Multicast
Max. User Access	10 Users / 20 Users
Edge Storage	NAS Local PC for instant recording Mirco SD card 128GB
Web Viewer	IE, Chrome, Firefox, Safari
Management Software	HD-VMS & VMS-PRO
Smart Phone	IOS, Android
Certifications	
Certifications	CE, FCC, RoHS
Interface	
Video Interface	1 Port(For adjustment only)
Audio Interface	1/1 channel In/Out
RS485	N/A
Alarm	2 channel In: 5mA 5VDC / 1 channel Out: 300mA 12VDC
Electrical	
Power Supply	DC12V, PoE (802.3af)(Class 0)
Power Consumption	<12.95W
Environmental	
Operating Conditions	-30° C ~ +60° C (-22° F ~ +140° F) Less than 95% RH
Storage Conditions	-30° C ~ +60° C (-22° F ~ +140° F) Less than 95% RH
Protection Level	Ingress Protection – IP67
Vandal Resistance	N/A
Construction	
Casing	Metal
Dimensions	273.2mm×95.0mm×95.0mm (10.76"×3.74"×3.74")
Net Weight	1.11Kg (2.44lb)
Gross Weight	1.51Kg (3.33lb)

All logos & trade marks represent the registered users only. All rights reserved.
All product specifications on this brochure are subject to change without notice.

CANADA:
351 Ferrier Street, Unit 5
Markham, ON L3R 5Z2
Toll Free: 1-866-843-6865
Tel: 416-410-6865

USA:
171 Cooper Ave. Suite 110
Tonawanda, NY 14150 USA
Toll Free: 1-866-843-6865
Local: 1-716-877-7277

Rev May 24, 2019
info@watchnetinc.com
www.watchnetinc.com

INDIA:
RZ- 2, Ground Floor
Kapashera
Opp Kapashera Police Station
New Delhi-110037
Tel/Fax: +91 11 26816005

UAE:
PO Box 126312
No 703, Oxford Towers
Business Bay
Dubai, UAE
Tel: +971 4 2767117