

# -GENESIS-

## General Purpose Security & Control Cable

Part Number: 1273

### 18 AWG 2 Stranded Individually Shielded Pairs

**Ratings** CM, CL2, Sunlight Resistant

**Approvals** ETL Listed

#### Construction

Conductor 18 AWG 19 Strand Bare Copper

Conductor Count 4 (2-pairs)

Insulation Polypropylene (0.006" nom.)

Insulation Colors Black/Red, Black/White

Lay Length 2.50" nom. (twist); 2.75" nom. (cable)

Shielding Aluminum Foil/Mylar w/ 24 AWG Tinned-Copper Drain

Rip Cord Yes

Jacket PVC (0.015 " nom.)

Overall Diameter 0.198" nom.

Print Legend GENESIS P/N 1273 2PR18 SHIELDED 3038058 (ETL) CL2 OR CM C(ETL)US SUN RES  
(RoHS) W/O #XXXXXXX-XXXXXX XXXX FT DEVICE/ZONE A B C D E F 1 2 3 4 5 6 7 8 9

#### Properties

Operating Voltage 300 Volts max.

DC Resistance 6.66 Ohms/1000' at 20°C

Capacitance 42.9 pF/ft. nom.

Impedance 36 Ohms nom.

Temperature -20°C to 60°C

Flame Rating UL 1685 Vertical Tray

RoHS Compliant Yes

Country of Origin USA