

-GENESIS-

Riser Rated Profusion® Access Control Cable Part Number: 2195

22/6 Stranded Shielded, 22/4 Stranded, 22/2 Stranded, 18/4 Stranded

Ratings CMR, CL3R, FT4, Sunlight Resistant
Approvals ETL Listed

Construction

Component	Door Strike	Card Reader	Door Contact	Request to Exit
Conductor	18 AWG 19 Strand Bare Copper	22 AWG 7 Strand Bare Copper	22 AWG 7 Strand Bare Copper	22 AWG 7 Strand Bare Copper
Conductor Count	4	6	2	4
Insulation	PP	PP	PP	PP
Insulation Colors	Black, Red, White, Green	Black, Red, White, Green, Brown, Blue	Black, Red	Black, Red, White, Green
Shielding	N/A	Aluminum Foil/Mylar with Drain	N/A	N/A
Rip Cord	Yes	Yes	Yes	Yes
Jacket / Color	PVC / Orange	PVC / White	PVC / Blue	PVC / Green
Assembly	Four components are cabled			
Overall Jacket Type / Diameter	None - Profusion® Jacketless Technology / 0.350" nom.			

Print Legends

GENESIS DOOR STRIKE P/N 2115 4C 18AWG 3038058 (ETL) CL3R OR FPLR OR CMR C(ETL)US FT4 SUN RES 75C (RoHS)
W/O# XXXXXX-XXXXXXX XXXXFT A B C D E F 1 2 3 4 5 6 7 8 9

GENESIS CARD READER P/N 2206 6C 22AWG SHIELDED 3038058 (ETL) CL3R OR FPLR OR CMR C(ETL)US FT4 SUN RES 75C (RoHS)
W/O# XXXXXX-XXXXXXX XXXXFT A B C D E F 1 2 3 4 5 6 7 8 9

GENESIS DOOR CONTACT P/N 2102 2C 22AWG 3038058 (ETL) CL3R OR FPLR OR CMR C(ETL)US FT4 SUN RES 75C (RoHS)
W/O# XXXXXX-XXXXXXX XXXXFT A B C D E F 1 2 3 4 5 6 7 8 9

GENESIS REQUEST-TO-EXIT P/N 2104 4C 22AWG 3038058 (ETL) CL3R OR FPLR OR CMR C(ETL)US FT4 SUN RES 75C (RoHS)
W/O# XXXXXX-XXXXXXX XXXXFT A B C D E F 1 2 3 4 5 6 7 8 9

Properties

Component	Door Strike	Card Reader	Door Contact	Request to Exit
Operating Voltage	300 Volts max.	300 Volts max.	300 Volts max.	300 Volts max.
DC Resistance @20°C	6.5 Ohms/1000' nom.	16.5 Ohms/1000' nom.	16.5 Ohms/1000' nom.	16.5 Ohms/1000' nom.
Capacitance	24 pF/ft. nom.	32 pF/ft. nom.	15 pF/ft. nom.	15 pF/ft. nom.
Impedance @20°C	42 Ohm. nom.	47 Ohms nom.	100 Ohms nom.	100 Ohms nom.

Temperature -20°C to 75°C
Flame Rating UL 1666 (Riser); CSA C22.2 No. 2556 (FT4)
RoHS Compliant Yes
Country of Origin USA