

Detailed Specification & Technical Data



424605P

4 Pair 23AWG UTP Category 6 OSP

10/100/1000 BaseT Ethernet, IP CCTV, Digital Integration, HDBaseT
The Cable is suitable for use in wet Locations and suitable for use outdoor in duct and aerial lashing
It is fully water blocked and has a sunlight resistant jacket

Construction & Dimensions

CONDUCTOR PARAMETERS		-
Number Of Pairs		4
AWG Size		23
Conductor Stranding		Solid
Conductor Type		Bare Copper
Nominal DCR		22 Ohm/1000ft
INSULATION PARAMETERS		-
Insulation Type		Polyolefin
Insulation Color Code		1.Blue,WH-Blue 2.Orange,WH-Orange 3.Green,WH-Green 4.Brown, WH-Brown
SHIELDING PARAMETERS		-
Shield Type		Unshielded Twisted Pair (UTP)
Flooding Compound		Yes - Water Blocking Compound
ELECTRICAL CHARACTERISTICS		-
Nominal Impedance		100 Ohm
Nominal Capacitance Between Conductors		14 pF/ft

Overall Construction

OVERALL CONSTRUCTION PARAMETERS		-
Total Number of Conductors		8
Jacket Type		UV Resistant PE
Nominal Cable O.D.		0.255 in
Plenum		No
NEC UL Rating		Outdoor
ANSI/TIA Category		Category 6 TIA/EIA 568C.2
TIA Test		ANSI/TIA-568-C.2
Pull Tension		35 lbs
Bend Radius		1.275 in
Cable Weight		39 lbs

Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS		-
Nominal Velocity of Propagation (VP)		72 %
Delay Skew		30 ns/100m
Operating Range		-20 to 60 Deg C
UL Voltage Rating		300



Electrical Performance

Frequency (Mhz)	Max. Insertion Loss	Min. NEXT	Min. PSNEXT	Min. PSACR	Min. ACR	Min. PSACRF (PSELF-EXT)	Min. ACRF (ELF-EXT)	Min. RL (Return Loss)	Max/Min Input Imp. Unfit	Max/Min Fitted Imp.
1 MHz	2 db/100m	75.3 dB	73.3 dB	71.3 dB	73.3 dB	67.8 dB	70.8 dB	20 dB	100 ± 15 Ohm	100 ± 15 Ohm
4 MHz	3.7 db/100m	66.3 dB	64.3 dB	60.6 dB	62.6 dB	55.8 dB	58.8 dB	23 dB	100 ± 15 Ohm	100 ± 15 Ohm
8 MHz	5.2 db/100m	63.3 dB	61.3 dB	56.1 dB	58.1 dB	49.7 dB	52.7 dB	24.5 dB	100 ± 15 Ohm	100 ± 15 Ohm
10 MHz	5.8 db/100m	61.8 dB	59.8 dB	54 dB	56 dB	47.8 dB	50.8 dB	25 dB	100 ± 15 Ohm	100 ± 15 Ohm
16 MHz	7.4 db/100m	58.6 dB	56.6 dB	49.2 dB	51.2 dB	43.7 dB	46.7 dB	25 dB	100 ± 15 Ohm	100 ± 15 Ohm
20 MHz	8.3 db/100m	57.1 dB	55.1 dB	46.8 dB	46.8 dB	41.8 dB	44.8 dB	25 dB	100 ± 15 Ohm	100 ± 15 Ohm
25 MHz	9.3 db/100m	55.5 dB	53.5 dB	44.3 dB	46.3 dB	39.8 dB	42.8 dB	24.3 dB	100 ± 15 Ohm	100 ± 15 Ohm
31.25 MHz	11.4 db/100m	54 dB	52 dB	41.6 dB	43.6 dB	37.9 dB	40.9 dB	23.6 dB	100 ± 15 Ohm	100 ± 15 Ohm
62.5 MHz	15 db/100m	49.1 dB	47.1 dB	32.1 dB	34.1 dB	31.9 dB	34.9 dB	21.5 dB	100 ± 15 Ohm	100 ± 15 Ohm
100 MHz	19.3 db/100m	45.8 dB	43.8 dB	24.5 dB	26.5 dB	27.8 dB	30.8 dB	20.8 dB	100 ± 15 Ohm	100 ± 15 Ohm
155 MHz	24.5 db/100m	42.7 dB	40.7 dB	16.2 dB	18.2 dB	24 dB	27 dB	19.8 dB	100 ± 15 Ohm	100 ± 15 Ohm
200 MHz	28.3 db/100m	40.9 dB	38.9 dB	10.6 dB	12.6 dB	21.8 dB	24.8 dB	18.7 dB	100 ± 22 Ohm	100 ± 15 Ohm
250 MHz	32.1 db/100m	39.3 dB	37.3 dB	5.2 dB	7.2 dB	19.8 dB	22.8 dB	18 dB	100 ± 32 Ohm	100 ± 15 Ohm
300 MHz	38 db/100m	38.1 dB	36.1 dB	-0.5 dB	2.5 dB	18.3 dB	21.3 dB	17.5 dB	100 ± 32 Ohm	100 ± 15 Ohm
350 MHz	38.9 db/100m	37.1 dB	35.1 dB	-3.7 dB	-1.7 dB	16.9 dB	19.9 dB	17 dB	100 ± 32 Ohm	100 ± 15 Ohm
400 MHz	42 db/100m	36.3 dB	34.3 dB	-7.7 dB	-5.7 dB	15.8 dB	18.8 dB	16.6 dB	100 ± 32 Ohm	100 ± 15 Ohm
450 MHz	45 db/100m	35.5 dB	33.5 dB	-11.5 dB	-9.5 dB	14.7 dB	17.7 dB	16.2 dB	100 ± 32 Ohm	100 ± 15 Ohm
500 MHz	47.9 db/100m	34.8 dB	32.8 dB	-15 dB	-13 dB	13.8 dB	16.8 dB	15.9 dB	100 ± 32 Ohm	100 ± 15 Ohm
550 MHz	50.6 db/100m	34.2 dB	32.2 dB	-18.4 dB	-16.4 dB	13 dB	16 dB	15.6 dB	100 ± 32 Ohm	100 ± 15 Ohm
Tested to 550Mhz - Values above 250Mhz are for Engineering Purposes Only										

Related Products

RELATED PRODUCTS	
Plenum Number	254246
Non Plenum Number	4246
Indoor/Outdoor Non Aquaseal	4246IO
Jack	KJ458MT-C6C-XX
Modular Plug	32-6EZP
Modular Plug 2	32-6198UL

Part Numbers

Part Number	Jacket Color	Put Up Length
4246OSPBK1000	BLACK	1000