



813

RG58/U 50 Ohm
 RF 50 Ohm Video, Wireless Mic Distribution

Construction & Dimenstions

CONSTRUCTION & DIMENSIONS	-
CONDUCTOR PARAMETER	-
• Number of Conductors	1
• AWG Size	20
• Conductor Stranding	Solid
• Conductor Type	Tinned Copper
• Nominal DCR	10.1 Ohm/1000ft
INSULATION PARAMETER	-
• Insulation Type	Foam Polyethylene
• Insulation Thickness	0.116 in
SHIELDING PARAMETER	-
• Shield Type	100% Aluminum Foil + 95% Tinned Copper Braid
ELECTRICAL CHARACTERISTICS	-
• Nominal Impedance	52 Ohm
• Nom. Cap. Between Conductors	25 pF/ft

Overall Construction

OVERALL CONSTRUCTION PARAMETERS	-
Jacket Type	PVC
Jacket Thickness	0.031 in
Nominal Cable O.D.	0.195 in
Plenum	No
NEC UL Rating	CM
RoHS Compliant	Yes
Pull Tension	45 lbs
Bend Radius	1.95 in
Cable Weight	30 lbs

Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
Nominal Velocity of Propagation (VP)	80 %
Delay Skew	1.54 ns/ft
UL Flammability	UL1685
Operating Range	-40 to 75 Deg C
UL Voltage Rating	300



813

Attenuation Performance

FREQUENCY (MHz)	ATTENUATION (db/100ft)
1 MHz	0.6 dB
10 MHz	1.5 dB
50 MHz	3.5 dB
100 MHz	4.7 dB
200 MHz	6.9 dB
400 MHz	10.2 dB
900 MHz	16.8 dB
1000 MHz	18.3 dB

Power Rating

Related Products

RELATED PRODUCTS	
BNC Crimp	CN-BM53-13