



AQ293

18/2 Shielded Indoor/Outdoor Direct Burial CL3/FPL Rated
 Audio, Control, Alarm Direct Burial



Construction & Dimensions

CONSTRUCTION & DIMENSIONS	-
CONDUCTOR PARAMETER	-
• Number of Conductors	2
• AWG Size	18
• Conductor Stranding	7x26
• Conductor Type	Bare copper
• Nominal DCR	6.2 Ohm/1000ft
INSULATION PARAMETER	-
• Insulation Type	PVC-Nylon
• Insulation Thi kness	0.02 in
• Insulation Color Code	1. Black 2.Red
SHIELDING PARAMETER	-
• Shield Type	Overall 100% Aluminum Foil
• Shield Type 2	Aquaseal Water Blocking Tape
• Drain Wire Type	Tinned Copper
• Drain Wire AWG	24 AWG
ELECTRICAL CHARACTERISTICS	-
• Nom. Cap. Between Conductors	32 pF/ft
• Nom. Cap. Conductor to Shield	58 pF/ft

Overall Construction

OVERALL CONSTRUCTION PARAMETERS	-
Jacket Type	UV Resistant PVC
Jacket Thi kness	0.04 in
Nominal Cable O.D.	0.31 in
Plenum	No
NEC UL Rating	CL3, FPL, PLTC
RoHS Compliant	Yes
TIA Test	TIA455-82 Water Penetration Test
Pull Tension	57 lbs
Bend Radius	2.79 in
Cable Weight	49 lbs

Overall Electrical & Optical Characteristics

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	-
UL Flammability	UL1685
Operating Range	-20 to 90 Deg C

Detailed Specification & Technical Data



AQ293

18/2 Shielded Indoor/Outdoor Direct Burial CL3/FPL Rated
Audio, Control, Alarm Direct Burial

Related Products

RELATED PRODUCTS	-
Plenum Number	25293B
Non Plenum Number	293
Aquaseal Number	AQC293
3 Pin XLR Male	CN-NC3MX
3 Pin XLR Female	CN-NC3FX
3.5mm Stereo Mini	CN-NYS231