

# AXIS FA4115 Dome Sensor Unit

Flexible, discreet indoor 1080p varifocal dome

AXIS FA4115 is a compact varifocal dome sensor unit for discreet indoor video surveillance in stores, offices and banks. For use with an AXIS FA Main Unit, AXIS FA4115 provides a 1080p resolution and flexible viewing angles ranging from a 53° to 99° horizontal field of view. A narrower field of view enables finer details to be captured. In wide mode, more of a scene can be covered. AXIS FA4115 uses Forensic WDR (wide dynamic range) that is tuned for motion. The unit comes with a mounting bracket and an 8-m (26 ft) cable for connection to a main unit.

- > **Flexible, compact dome for indoor surveillance**
- > **Varifocal lens with 1080p resolution**
- > **99° –53° horizontal field of view**
- > **Forensic WDR**
- > **Axis Corridor Format for vertically oriented coverage areas**



## AXIS FA4115 Dome Sensor Unit

Camera		General	
<b>Image sensor</b>	1/3" (effective) progressive scan RGB CMOS	<b>Casing</b>	Aluminum Plastic
<b>Lens</b>	Fixed iris, varifocal 2.8–6.0 mm, F2.0 Horizontal field of view: 99°–53° Vertical field of view: 53°–30°	<b>Sustainability</b>	PVC free
<b>Resolution</b>	1920x1080 (1080p)	<b>Operating conditions</b>	-20 °C to 50 °C (-4 °F to 122 °F) Humidity 10–85% RH (non-condensing)
<b>Wide dynamic range</b>	Forensic WDR	<b>Storage conditions</b>	-40 °C to 65 °C (-40 °F to 149 °F)
<b>Minimum illumination</b>	Color: 0.2 lux	<b>Approvals</b>	EMC 55032 Class B, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class B, VCCI Class B, RCM AS/NZS CISPR 32 Class B, ICES-003 Class B
<b>Shutter time</b>	1/32500 s to 1/25 s with 50 Hz 1/32500 s to 1/30 s with 60 Hz	<b>Safety</b>	IEC/EN/UL 62368-1
<b>Camera angle adjustment</b>	Pan: 360° Tilt: 0° to 90° Rotation: 360°	<b>Environment</b>	EN 50581, IEC 60529 IP3X, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14, IEC 60068-2-78, IEC 60068-2-6, IEC 60068-2-27
<b>Frame rate</b>	Max 25/30 fps (50/60 Hz)	<b>Dimensions</b>	Height: 50 mm to 70 mm (2 in to 2 13/16 in) ø 88 mm (3 8/16 in)
		<b>Weight</b>	112 g (0.25 lb)
		<b>Required hardware</b>	AXIS FA Main Unit
		<b>Included accessories</b>	Installation Guide 8-m (26 ft) black cable, mounting brackets
		<b>Optional accessories</b>	AXIS F7315 Cable White 15 m
		<b>Warranty</b>	Axis 3-year warranty and AXIS Extended Warranty option, see <a href="http://www.axis.com/warranty">www.axis.com/warranty</a>

Environmental responsibility:

[www.axis.com/environmental-responsibility](http://www.axis.com/environmental-responsibility)