



The Single Point, Wide-Coverage Solution

Listening to music outdoors and in large interior spaces has always been a problem. Move off-center and you miss critical information. But we've solved all that. With just one Proficient AW500TT, you get even dispersion throughout the listening area.

In a word, it's unique. Our dual voice coil, twin tweeter system masters the challenges of outdoor sound and wide-coverage installations, with a degree of dispersion that conventional stereo speaker systems can't match. We call it "constant directivity". You'll call it amazing.

The AW500TT really cranks out the bass, even at low listening levels. Plus, it has twin 1" soft dome, pivoting tweeters mounted in Slant-Back wave planes for enhanced high-frequency dispersion. So you'll get great coverage no matter where you are.

The AW500TT is our flagship in a complete line of high-performance, weather-resistant speakers. For stereo speaker applications, the AW525 and AW650 speaker pairs are excellent indoors or out, providing superb imaging and staging across the sound field.

AW Series speakers are built to last, too. They'll take the heat — and the cold — for years to come.

Quality-built, of course. Exactly what you'd expect from a premium brand like Proficient.



AW500TT
5 1/4" Twin Tweeter
Indoor/Outdoor
Wide Coverage
Single Speaker
Black or White



AW650
6 1/2" 2-Way
Indoor/Outdoor
Stereo Pair



AW525
5 1/4" 2-Way
Indoor/Outdoor
Stereo Pair
Black or White

PROFICIENT[™]
Audio Systems
proficientaudio.com

PROFICIENT™ Audio Systems



AW500TTblk/wht

AW525blk/wht

AW650

	AW500TTblk/wht	AW525blk/wht	AW650
Description	Constant Directivity, Twin Tweeter Dual Voice Coil Speaker	5¼" Two Way Indoor / Outdoor Speakers	6½" Two Way Indoor / Outdoor Speakers
Wiring	Four Conductor (Left and Right)	Left: 2 Conductor Right: 2 Conductor	Left: 2 Conductor Right: 2 Conductor
Unit of Measure	Each	Pair	Pair
Brackets	Included	Included	Included
Woofer Size	5¼"	5¼"	6½"
Woofer	Polypropylene Cone with Dual Voice Coil and Butyl Rubber Surround	Polypropylene Cone with Butyl Rubber Surround	Polypropylene Cone with Butyl Rubber Surround
Tweeter(s)	Two 1" Supernil Soft Dome	1" Supernil Soft Dome	1" Supernil Soft Dome
Pivoting Tweeter	Yes	Yes	Yes
Power Handling	100 Watts	125 Watts	150 Watts
Freq Response	38Hz-20kHz	45Hz-20kHz	37Hz-20kHz
Sensitivity	89dB	88dB	89dB
Impedance	4Ω	8Ω	4Ω
Warranty	10-Year Limited	10-Year Limited	10-Year Limited