



SW2600AC

Resolution	Standard 520TVL	Hi-Res 600TVL
Min Illumination	0.1 Lux	0.8Lux
S/N Ratio	≥48dB	
Video Output	1.0Vp-p/75Ω	
White Balance	Auto	
Backlight Compensation	Auto	
Electronic Shutter	1/50 (1/60) ~ 1/1000000	
Gamma Correction	0.45	
Lens	3.7mm	
Power Consumption	12Vdc 150mA	

SW2600ACTR

	Standard	Hi-Power
Max TX Output	10dBm	100mW
Power Consumption	12Vdc @ 150mA	12Vdc @ 300mA
Useable Channel	4	80
Receiver Sensitivity	-80dBm min	-80dBm min
Operating Range	700ft Line of sight	1500ft Line of sight

SW2600DVR

System	NTSC
Codec	Mpeg4-SP ASF File Format
Record Frame Rate	Selectable up to 12FPS
Record Quality	Low/Med/High
Time/Date	Overlay with Video Images in ASF File
Input	From Built-in Camera
Output	1Ch composite Video Line Out, 1Vp-p/75Ω
Storage Device	SD Card (up to 32Gb), 4GB included
Record Mode	Manual, Schedule (alarm, motion detection, continues)
Playback Speed	1X, 2X, 4X, 8X, 16X, 32X