

DESCRIPTION

The ASK-4® #631 is a single zone audio monitoring system with a wall mounted mute switch. This system is designed to interface with a DVR, VCR or other recording devices that accept line level input. The IF-1 Audio Interface Adapter provides power to the microphone and gain controlled audio output to the receiving device such as an IP camera or DVR. The Verifact® A is an omnidirectional pre-amplified microphone that produces line level output. The MS-1 is an illuminated mute switch that can mute microphone output to recorder and is commonly used for interrogation rooms.

KIT CONTENTS

- Verifact® Model A Microphone
- Model IF-1 Audio Interface Adapter
- Model MS-1 Mute Switch
- Model AD-1 12Vdc power supply
- Single RCA cable
- 3.5mm Stereo Cable
- RCA to 3.5mm Mono Adaptor

APPLICATION

The ASK-4® #631 can be used in situations such as:

- Convenience Stores
- Fast Food Restaurants
- Customer Service Counters
- Cashier Booths

2 Conductor shielded cable, 22 gauge with a 24 gauge drain wire
West Penn 452 or equiv)
(not supplied by Louroe)

WIRING REQUIREMENTS

IMPORTANT NOTICE

When this equipment is used as part of an audio monitoring system, the law requires that the public be given notice of AUDIO MONITORING ON THE PREMISES. A decal notice is included with each microphone shipped.



Federal Law References:
Federal Regulations, US Code, Title 18. Crime and Criminal Procedure, Sec 2510.



SPECIFICATIONS (MS-1 Mute Switch)

■ Supply Voltage	12Vdc
■ Dimensions	2 3/4" W x 4 1/2" H
■ Faceplate	303 Stainless Steel
■ Backbox	Single gang electrical box (not included)
■ Weight	2.5 oz



IF-1 Audio Interface Adapter



AD-1



MS-1 Mute Switch



VERIFACT® A

FEATURES

- Omni-directional microphone can pick up normal sounds 15' away or within a 30' diameter circle.
- Model IF-1 Audio Interface Adapter provides power to the microphones.
- Contains gain adjust for each microphone output to prevent overdriving of signal into a DVR, soundcard, IP Network Camera, etc.
- Mute switch turns off the microphone when it is not needed
- 12Vdc/110V power supply included
- Connector cables from audio output of IF-1 to audio input of recording device included

SPECIFICATIONS (IF-1 Interface Adapter)

■ Input impedance	17.5 KΩ @ 1kHz
■ Output impedancel	600Ω @1kHz
■ Power supply	12Vdc, 500 mA
■ Dimensions	6 1/8"L x 4 5/8"W x 1 3/8"H
■ Audio output gain	up to +10dB
■ Weight	5.5 oz

SPECIFICATIONS (Microphone - Model A)

■ Type	Electret Condenser
■ Output	Line Level (0 dB 600Ω @ 1 kHz)
■ Frequency response	50 Hz to 15 kHz ± 1 dB
■ Current drain	10 mA
■ Supply voltage	12Vdc
■ Dimensions	4"Dia x 1 1/2"H
■ Weight	3.5 oz
■ Shipping Weight of kit	2 lbs