Quam system 6VPS

The SYSTEM 6VPS is a complete, vandal resistant horn assembly featuring a double re-entrant, compression horn with an integrated 16W, 25/70V, multi-tap transformer that is mounted on a vandal resistant, stainless steel baffle. It also includes a square, heavy gauge stainless steel, surface mount enclosure with four (4) threaded inserts for baffle attachment, a single ½" conduit entrance and a Wiremold entrance on the top and bottom. Tamper resistant, 8-32 x 1", 'pin-in-torx' screws are included. It has a high durability, white, powder coat finish.



APPLICATION Intended Use: Indoor or outdoor environment

Program Material: Signal tones, and voice

Installation: Vertical or horizontal surface mount

AUDIO Average Sensitivity: 110dB SPL, 1W/1M

Loudspeaker Power Rating: 16W RMS, EIA 426A Standard

Calculated Output: 121dB SPL, 16W/1M

Magnet Type & Weight:BeFe Ceramic, 5 oz. NominalFrequency Response:350Hz - 10kHz, EIA 426A StandardNominal Coverage Angle:90° Included Angle, -6dB/2kHz, Half Space

Audio Connection: 7", Color-coded, Pre-tinned Leads

COMPONENT

PERFORMANCE

Dimensions: 11 %" (H) x 11 %" (W) x 4 %" (D)

Weight: 12 lbs. Loudspeaker Model: H16

Loudspeaker Specs: Double re-entrant horn

Transformer: 16W, 25/70V, with 5 taps (1W, 2W, 4W, 8W, 16W)

Baffle:BS8VPS: square, stainless steelEnclosure:SE1WVPS, stainless steelFinish:White powder coat finish

Other: Tamper resistant, 8-32x1" 'pin-in-torx' hardware included













