

6.0MP MegaPixel
360° Panoramic View
Ultra HD Camera




MPix-60-360-FIR



6Mp 360° Panoramic View
Fisheye Lens IR Dome Camera

Features:

- ❖ 1/1.8" 6M progressive scan CMOS sensor
- ❖ Low bitrate
- ❖ Excellent low light performance
- ❖ 3D DNR, D-WDR, ICR, HLC
- ❖ Lens - 1.6mm
- ❖ ONVIF system compatibility
- ❖ Max. Resolution - 3072x2048@15fps
- ❖ SD card storage
- ❖ 7 split display mode
- ❖ Panoramic view mode
- ❖ Built-in de-warping
- ❖ Dual stream
- ❖ Smart IR
- ❖ Electronic PTZ
- ❖ Audio recording
- ❖ Noise Reduction - 2D/3D
- ❖ IP66 weather proof



Optional Bracket:
BRACK-MX-60-360



FREE Multisite VMS Software included




Pendant Mounting Accessories


MULTIPLE VIEWING PATTERNS




Panoramic View 180°



Fish Eye View 360°



Fish Eye View + 3 split dewarped



Fish Eye View + 5 split dewarped



Fish Eye View + 7 split dewarped



Easy Web Configuration



WTC-A10K



WTC-PMA



Model	MPIX-60-360-FIR
Camera	
Panoramic View	
Image Sensor	1/1.8" 6Megapixel progressive scan CMOS
Max.Resolution	3072(H) x 2048(V)@15fps
Min. Illumination	Color 0.01Lux(AGC ON); IR ON 0 Lux
Electronic Shutter Speed	1/5-1/20000
Day & Night	ICR, Auto Iris
Scanning System	Progressive
Lens	
IR LED	6 pcs
Focal Length	Fisheye Lens: 1.6mm
Lens Type	M12
Video	
Video Compression	H.264 High/Main / Baseline Profile, MJPEG
Bit Rate (CBR/VBR)	500kb-12000kb
Frame Rate	Stream1: 3072 x 2048@15fps, 1920 x 1920 / 1440 x 1440 / 1920 x 1080@25fps/30fps Stream 2: 1280 x 1280 / 720 x 720 / 74 x 576@15fps/25fps/30fps
Image Setting	Rotate Mode, Saturation, Brightness, Contrast, Sharpness
De-warping	1F+3/5/7,180 degrees panorama
Camera Features	
Max. IR LEDs Length	10m
Backlight Compensation	HLC / D-WDR
FOV	360 degrees
Interface	
Ethernet	1 Ethernet (10/100 Base-T) / RJ-45 Connector
Edge Storage	Micro SD/SDHC/SDXC slot, Max 64GB
Audio	
Audio Compression	G.711, RAW PCM
Audio I/O	1ch Audio In, 1ch Audio Out
Alarm I/O	1ch Alarm In, 1ch Alarm Out
Network	
Alarm Trigger	Network disconnect, Disk alarm, I/O alarm
Network Functions	HTTP,HTTPS, TCP/IP, UDP/IP, RTSP, DHCP, NTP, PPPoE, Unicast and Multicast supported
RTSP Video	Standard RFC2326, Support QuickTime / VLC Player
Security	User security authentication, Reset, Hardware Watch Dog
Compatibility	ONVIF
Environmental	
Power Supply/Consumption	AC24V / DC12V / POE(802.3af) / 5W IR LED OFF; 8W IR LED ON
OperatingTemp./Hum.	-30°C ~ +60°C / -22°F ~ +140F, 0% ~ 90% RH
Vandal Resistance	IP66
Dimension	Φ160mm×46.8mm / 6.3" × 1.84"
Weight	0.700kgs / 1.54lb

All logos & trade marks represent the registered users only. All rights reserved.
All product specifications on this brochure are subject to change without notice.

CANADA:
351 Ferrier Street, Unit 5
Markham, ON L3R 5Z2
Toll Free: 1-866-843-6865
Tel: 416-410-6865
Fax: 1-866-331-3341

USA:
171 Cooper Ave. Suite 110
Tonawanda, NY 14150 USA
Toll Free: 1-855-404-3193
Local: 1-716-877-7277
Fax: 1-866-331-3341

info@watchnetinc.com
www.watchnetinc.com

INDIA:
RZ- 2, Ground Floor,
Kapashera
Opp Kapashera Police Station
New Delhi-110037
Tel/Fax: +91 11 26816005

UAE:
P O Box 126312
No 703, Oxford Towers
Business Bay
Dubai, UAE