

Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Cat6 Gigabit Molded (UTP) Ethernet Cable (RJ45 M/M), Blue, 10 ft. (3.05 m)

MODEL NUMBER: N200-010-BL



Ideal for connecting high-speed network components, such as computers, printers, video game systems, Blu-ray™ players, copy machines, routers and modems, in a home or office Cat5/5e/6 application.

Description

The N200-010-BL Cat6 Gigabit Molded Patch Cable (M/M) ensures ultra-fast performance throughout your Cat5/5e/6 network application. It connects high-speed network components like computers, printers, video game systems, Blu-ray players, copy machines, routers and modems in a home or office Cat5/5e/6 application.

This 10-ft. (3.05 m) blue cable is designed for 1000Base-T (1 Gbps Ethernet), 10/100Base-T (Ethernet), 100 Mbps TPDDI, 155 Mbps ATM, ISDN, voice, Token Ring Type 3 and EIA/TIA applications.

Manufactured from 24 AWG 4-pair stranded UTP with a staggered-pin plug design and male RJ45 connectors, each cable provides high-speed connections up to 550 MHz/1 Gbps and flawless signal delivery, while keeping near-end crosstalk levels to a minimum.

The N200-010-BL is constructed of top-quality materials for long life and durability. Corrosion-resistant gold-plated copper contacts provide maximum conductivity and minimize data loss. Integral strain relief gives the cable extra flexibility, reduces stress, and helps the cable and connectors move freely without cracking. Meets most current industry standards, including IEEE 802.3ab, IEEE 802.5, ANSI/EIA/TIA 568, ISO/IEC 11801 and ETL (category 6 draft 11).

Features

The Ideal Solution for All High-Speed Cat5/5e/6 Networking

- Connects high-speed network components, such as computers, printers, video game systems, Blu-ray players, copy machines, routers and modems
- Designed for 1000Base-T, 10/100Base-T (Ethernet), 100 Mbps TPDDI, 155 Mbps ATM, ISDN, voice,
 Token Ring Type 3 and EIA/TIA applications

Highlights

- Premium cabling for Cat5/5e/6 home/office network applications
- Rated for 550 MHz/1 Gbps communication
- 24 AWG 4-pair stranded UTP with PVC jacket
- Gold-plated copper contacts minimize data loss
- Integral strain relief protects connectors from stress and cracking

Package Includes

N200-010-BL Cat6 Gigabit
 Molded Patch Cable, Blue, 10-ft.
 (3.05 m)



- Recommended for home or office applications
- Provides high-speed connections up to 550 MHz/1 Gbps
- Flawless signal delivery with minimal near-end crosstalk levels

Premium Construction Ensures Error-Free Signal Transfer

- Manufactured from 24 AWG 4-pair stranded UTP with staggered-pin plug design
- Molded RJ45 connectors and gold-plated copper contacts for maximum conductivity and minimum data loss
- Integral strain relief protects cable and connectors from stress and cracking
- Meets most current industry standards, including IEEE 802.3ab, IEEE 802.5, ANSI/EIA/TIA 568, ISO/IEC 11801 and ETL (category 6 draft 11)

Specifications

UPC Code 037332194527 Technology Cat6 PHYSICAL Color Blue Cable Shielding UTP Cable Jacket Material PVC Cable Jacket Rating CM Number of Conductors 4 Pair Conductor Material Stranded Copper Conductor Gauge 24 AWG Cable Length (ft.) 10 Cable Length (m) 3 Cable Length (in.) 120 Cable Length (cm) 304.8 Shipping Dimensions (hwd / cm) 17.78 x 22.86 x 1.27 Shipping Dimensions (hwd / in.) 7.00 x 9.00 x 0.50 Shipping Weight (kg) 0.13 Shipping Weight (lbs.) 0.29		
PHYSICAL	OVERVIEW	
PHYSICAL Color Blue Cable Shielding UTP Cable Jacket Material PVC Cable Jacket Rating CM Number of Conductors 4 Pair Conductor Material Stranded Copper Conductor Gauge 24 AWG Cable Length (ft.) 10 Cable Length (m) 3 Cable Length (in.) 120 Cable Length (cm) 304.8 Shipping Dimensions (hwd / cm) 17.78 x 22.86 x 1.27 Shipping Dimensions (hwd / in.) 7.00 x 9.00 x 0.50 Shipping Weight (kg) 0.13 Shipping Weight (lbs.) 0.29	UPC Code	037332194527
Color Blue Cable Shielding UTP Cable Jacket Material PVC Cable Jacket Rating CM Number of Conductors 4 Pair Conductor Material Stranded Copper Conductor Gauge 24 AWG Cable Length (ft.) 10 Cable Length (m) 3 Cable Length (in.) 120 Cable Length (cm) 304.8 Shipping Dimensions (hwd / cm) 17.78 x 22.86 x 1.27 Shipping Dimensions (hwd / in.) 7.00 x 9.00 x 0.50 Shipping Weight (kg) 0.13 Shipping Weight (lbs.) 0.29	Technology	Cat6
Cable Shielding UTP Cable Jacket Material PVC Cable Jacket Rating CM Number of Conductors 4 Pair Conductor Material Stranded Copper Conductor Gauge 24 AWG Cable Length (ft.) 10 Cable Length (m) 3 Cable Length (in.) 120 Cable Length (cm) 304.8 Shipping Dimensions (hwd / cm) 17.78 x 22.86 x 1.27 Shipping Dimensions (hwd / in.) 7.00 x 9.00 x 0.50 Shipping Weight (kg) 0.13 Shipping Weight (lbs.) 0.29	PHYSICAL	
Cable Jacket Material PVC Cable Jacket Rating CM Number of Conductors 4 Pair Conductor Material Stranded Copper Conductor Gauge 24 AWG Cable Length (ft.) 10 Cable Length (m) 3 Cable Length (in.) 120 Cable Length (cm) 304.8 Shipping Dimensions (hwd / cm) 17.78 x 22.86 x 1.27 Shipping Dimensions (hwd / in.) 7.00 x 9.00 x 0.50 Shipping Weight (kg) 0.13 Shipping Weight (lbs.) 0.29	Color	Blue
Cable Jacket Rating CM Number of Conductors 4 Pair Conductor Material Stranded Copper Conductor Gauge 24 AWG Cable Length (ft.) 10 Cable Length (m) 3 Cable Length (in.) 120 Cable Length (cm) 304.8 Shipping Dimensions (hwd / cm) 17.78 x 22.86 x 1.27 Shipping Dimensions (hwd / in.) 7.00 x 9.00 x 0.50 Shipping Weight (kg) 0.13 Shipping Weight (lbs.) 0.29	Cable Shielding	UTP
Number of Conductors 4 Pair Conductor Material Stranded Copper Conductor Gauge 24 AWG Cable Length (ft.) 10 Cable Length (m) 3 Cable Length (in.) 120 Cable Length (cm) 304.8 Shipping Dimensions (hwd / cm) 17.78 x 22.86 x 1.27 Shipping Dimensions (hwd / in.) 7.00 x 9.00 x 0.50 Shipping Weight (kg) 0.13 Shipping Weight (lbs.) 0.29	Cable Jacket Material	PVC
Conductor Material Stranded Copper Conductor Gauge 24 AWG Cable Length (ft.) 10 Cable Length (m) 3 Cable Length (in.) 120 Cable Length (cm) 304.8 Shipping Dimensions (hwd / cm) 17.78 x 22.86 x 1.27 Shipping Dimensions (hwd / in.) 7.00 x 9.00 x 0.50 Shipping Weight (kg) 0.13 Shipping Weight (lbs.) 0.29	Cable Jacket Rating	СМ
Conductor Gauge 24 AWG Cable Length (ft.) 10 Cable Length (m) 3 Cable Length (in.) 120 Cable Length (cm) 304.8 Shipping Dimensions (hwd / cm) 17.78 x 22.86 x 1.27 Shipping Dimensions (hwd / in.) 7.00 x 9.00 x 0.50 Shipping Weight (kg) 0.13 Shipping Weight (lbs.) 0.29	Number of Conductors	4 Pair
Cable Length (ft.) 10 Cable Length (m) 3 Cable Length (in.) 120 Cable Length (cm) 304.8 Shipping Dimensions (hwd / cm) 17.78 x 22.86 x 1.27 Shipping Dimensions (hwd / in.) 7.00 x 9.00 x 0.50 Shipping Weight (kg) 0.13 Shipping Weight (lbs.) 0.29	Conductor Material	Stranded Copper
Cable Length (m) 3 Cable Length (in.) 120 Cable Length (cm) 304.8 Shipping Dimensions (hwd / cm) 17.78 x 22.86 x 1.27 Shipping Dimensions (hwd / in.) 7.00 x 9.00 x 0.50 Shipping Weight (kg) 0.13 Shipping Weight (lbs.) 0.29	Conductor Gauge	24 AWG
Cable Length (in.) 120 Cable Length (cm) 304.8 Shipping Dimensions (hwd / cm) 17.78 x 22.86 x 1.27 Shipping Dimensions (hwd / in.) 7.00 x 9.00 x 0.50 Shipping Weight (kg) 0.13 Shipping Weight (lbs.) 0.29 COMMUNICATIONS	Cable Length (ft.)	10
Cable Length (cm) 304.8 Shipping Dimensions (hwd / cm) 17.78 x 22.86 x 1.27 Shipping Dimensions (hwd / in.) 7.00 x 9.00 x 0.50 Shipping Weight (kg) 0.13 Shipping Weight (lbs.) COMMUNICATIONS	Cable Length (m)	3
Shipping Dimensions (hwd / cm) 17.78 x 22.86 x 1.27 Shipping Dimensions (hwd / in.) 7.00 x 9.00 x 0.50 Shipping Weight (kg) 0.13 Shipping Weight (lbs.) COMMUNICATIONS	Cable Length (in.)	120
Shipping Dimensions (hwd / in.) 7.00 x 9.00 x 0.50 Shipping Weight (kg) 0.13 Shipping Weight (lbs.) COMMUNICATIONS	Cable Length (cm)	304.8
Shipping Weight (kg) 0.13 Shipping Weight (lbs.) 0.29 COMMUNICATIONS	Shipping Dimensions (hwd / cm)	17.78 x 22.86 x 1.27
Shipping Weight (lbs.) COMMUNICATIONS	Shipping Dimensions (hwd / in.)	7.00 x 9.00 x 0.50
COMMUNICATIONS	Shipping Weight (kg)	0.13
	Shipping Weight (lbs.)	0.29
Bandwidth per TIA Standard 250 MHz	COMMUNICATIONS	
	Bandwidth per TIA Standard	250 MHz





Maximum Bandwidth as Tested	500 MHz	
Maximum Data Rate	1Gbps	
Network Speed	1Gbps	
CONNECTIONS		
Side A - Connector 1	RJ45 (MALE)	
Side B - Connector 1	RJ45 (MALE)	
Connector Type	Molded	
Wiring Configuration	EIA/TIA 568B	
FEATURES & SPECIFICATIONS		
Cable Style	Unshielded; Molded	
SPECIAL FEATURES		
IP68 Rated	No	
Snagless Connector	No	
Antibacterial	No	
STANDARDS & COMPLIANCE		
Certifications	RoHS-Compliant	
Approvals	EIA/TIA Cat6 TIA/EIA- 568-B-2.1	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies