


# 7-Port Portable USB 3.0 SuperSpeed Mini Hub, Aluminum

## MODEL NUMBER: U360-007-AL











Connects to the USB 3.0 port on your laptop, Ultrabook or computer to give you 7 external USB 3.0 ports.

#### Description

The U360-007-AL 7-Port Portable USB 3.0 SuperSpeed Mini Hub's built-in USB cable connects to your laptop, Ultrabook or computer to provide seven available USB 3.0 ports. Just plug and play with no drivers or software needed. The included external power supply provides 5V 3A to be shared among all seven USB ports, with each port capable of providing up to 1.5A for fast charging of mobile devices. All seven ports support USB Battery Charging (BC) specification v1.2.

This portable hub supports USB 3.0 data transfer rates up to 5 Gbps—ten times faster than USB 2.0—and is backward compatible with USB 2.0 and USB 1.1 devices. The compact, lightweight aluminum case fits easily into your pocket, backpack, briefcase or laptop bag.

#### **Features**

Increases Your Computer's USB 3.0 Ports from 1 to 7Expands your laptop, Ultrabook or computer's USB 3.0 port to 7 external USB 3.0 portsIncluded external power supply provides 5V 3A to be shared among all portsEach port is capable of providing up to 1.5ASupports USB Battery Charging (BC) specification v1.2

**Excellent Speed and Versatile Performance**Supports USB 3.0 data transfer rates up to 5 Gbps—10 times faster than USB 2.0Backward compatible with USB 2.0 and USB 1.1

**Take the Hub Anywhere**Compact case made from lightweight aluminumFits easily into your pocket, backpack, briefcase or laptop bagBuilt-in cable is perfect for travel

### **Highlights**

- USB ports can provide up to 1.5A for charging mobile devices\*
- All seven ports support USB Battery Charging (BC) specification v1.2
- Supports USB 3.0 data transfer rates up to 5 Gbps
- Plug and play—no drivers or software needed
- Fits easily into pocket,
   backpack, briefcase or laptop
   baq
- Backward compatible with USB
   2.0 and USB 1.1

\*When using the included external power supply

#### **System Requirements**

 Device with USB port (USB 3.0 port needed to achieve USB 3.0 speeds)

### **Package Includes**

- U360-007-AL 7-Port Portable
   USB 3.0 SuperSpeed Mini Hub
- External power supply (Input: 100–240V, 50/60 Hz, 0.6A; Output: 5V 3A)

# **Specifications**

OVERVIEW	
UPC Code	037332201027
Product Type	Hub
AC Adapter	Input: 100-240V, 50/60Hz, 0.6A; Output: 5V, 3A



Technology	USB 3.0 (SuperSpeed); USB	
Host Connector	USB A (MALE)	
VIDEO		
Number of Monitors Supported	0	
Extended Mode	No	
Mirror Mode	No	
DATA		
Data Ports	(7) USB A (FEMALE)	
Data Ports Detail	(7) USB-A - USB 3.2 Gen 1 (5 Gbps)	
INPUT		
Voltage Compatibility (VAC)	100; 110; 120; 125; 127; 200; 208; 220; 230; 240	
External Power Supply Plug(s)	NEMA 1-15P North America	
Bus Powered	No	
Product Length (in.)	21.6	
Product Length (cm.)	54.86	
Product Length (ft.)	1.8	
Product Length (m.)	0.548	
POWER		
External Power Supply Input Specs (V / Hz / A)	100-240V / 50/60Hz / 0.6A	
External Power Supply Output Specs (V / A)	5V/3A	
External Power Supply Cord Length (ft.)	5	
External Power Supply Cord Length (m.)	1.5	
External Power Supply DC Barrel Connector Specs	OD: 3.5 x 1.35 x 10mm, Positive Pin, Negative Sleeve	
External Power Supply Certifications	CE; FCC; UL; cUL; TUV; CCC; RoHS	
USER INTERFACE, ALERTS & CON	TROLS	
LED Indicators	White (Power)	
CHARGING		
Charging Ports	USB-A: 5V 1.5A (7.5W)	
PHYSICAL		





Color	Black	
Cable Jacket Rating	VW-1	
Material of Construction	Aluminum	
Shipping Dimensions (hwd / cm)	5.59 x 11.18 x 19.56	
Shipping Dimensions (hwd / in.)	2.20 x 4.40 x 7.70	
Shipping Weight (kg)	0.39	
Shipping Weight (lbs.)	0.87	
Unit Dimensions (hwd / in.)	0.83 x 6.2 x 1.2	
Unit Packaging Type	Вох	
Unit Weight (kg)	0.24	
Unit Weight (lbs.)	0.53	
ENVIRONMENTAL		
Operating Temperature Range	-4 to 158 F (-20 to 70 C)	
Storage Temperature Range	14 to 158 F (-10 to 70 C)	
Relative Humidity	10% to 90% RH, Non-Condensing	
BTUs (Watta)	4.7 BTU/Hr	
Power Consumption (Watts)	1.4	
Power Provided to Connected Device(s)	5V 1.5A (7.5W) Output per USB Port	
CONNECTIONS		
Ports	7	
Side A - Connector 1	USB 3.0 A (MALE)	
Side B - Connector 1	(7) USB 3.0 A (FEMALE)	
Connector Plating	Nickel	
FEATURES & SPECIFICATIONS		
USB Specification	USB 3.0 (up to 5 Gbps); USB 3.1 Gen 1 (up to 5 Gbps)	
Driver Required	No	
STANDARDS & COMPLIANCE		
Certifications	Tested to CE, FCC, RoHS, REACH	
WARRANTY		
Product Warranty Period (Worldwide)	3-year limited warranty	

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <a href="https://www.tripplite.com/products/product-certification-agencies">https://www.tripplite.com/products/product-certification-agencies</a>