

## AXIS T91A23

### *Flexible mount for drop-ceiling tile grids*

AXIS T91A23 Tile Grid Ceiling Mount is a unique accessory designed for mounting Axis cameras and stands on a variety of drop-ceiling tile grid systems. With no need for drilling and minimum alteration to the ceiling, the mount helps to save time and money during installation. Whenever needed, the camera can be quickly repositioned along the grid rails to cover a new field of view. AXIS T91A23 is compatible with AXIS Safety Wire for a secure ceiling installation. The mount is ideal for retail, banking, commercial and education environments.

- > **Quick and instant grip to the tile grid**
- > **No drilling or damages to ceiling tiles**
- > **Easily reposition the camera when needed**
- > **Compatible with wide range of drop-ceiling systems**



## AXIS T91A23

**Models** AXIS T91A23 Tile Grid Ceiling Mount

**AXIS T91B21 Stand Black/White, required for:**  
AXIS P13 Series, AXIS Q16 Series

### General

<b>Mounting</b>	Compatible tile grids (T-bar rails): 15 mm (0.6 in), 24 mm (0.9 in), 35 mm (1.4 in) Compatible ceiling tiles: Square edge, Regular edge (max depth of 10 mm (0.4 in))	<b>Maximum load</b>	2000 g (4.4 lb)
<b>Supported products</b>	Directly compatible with: AXIS M2025-LE, AXIS M2026-LE Mk II, AXIS M3024-LVE, AXIS M3025-VE, AXIS M3026-VE, AXIS M3027-PVE, AXIS M3037-PVE, AXIS M3044-V, AXIS M3044-WV, AXIS M3045-V, AXIS M3045-WV, AXIS M3046-V, AXIS M3047-P, AXIS M3048-P, AXIS M3057-PLVE, AXIS M3058-PLVE, AXIS M3104, AXIS M3104-L, AXIS M3104-LVE, AXIS M3105, AXIS M3105-L, AXIS M3105-LVE, M3106-L Mk II, M3106-LVE Mk II, M5054, M5055, M5065, P3224-LV Mk II, P3224-V Mk II, P3225-LV Mk II, P3225-LVE Mk II, P3225-V Mk II, P3225-VE Mk II, P3227-LV, P3227-LVE, P3228-LV, P3228-LVE, P3367-V, P3374-LV, P3375-LV, P3375-V, AXIS Companion Dome V, AXIS Companion Dome WV, AXIS Companion 360, AXIS Companion Eye L, AXIS Companion Eye LVE, AXIS Companion Eye Mini L, AXIS Companion Bullet Mini LE AXIS T91A10 Mounting Kit, required for: AXIS M1045-LW, AXIS M1065-L, AXIS M1065-LW, AXIS F8205/F8215 with AXIS F1005-E, AXIS F8205/F8215 with AXIS F1015, AXIS F8205/F8215 with AXIS P1280-E, AXIS T8331, AXIS T8331-E AXIS T91A11 Stand White, required for: AXIS M10 Series, AXIS M11 Series, AXIS Companion Cube L, AXIS Companion Cube LW	<b>Environment</b>	Indoor
		<b>Casing</b>	Plastic Color: white NCS S 1002-B
		<b>Sustainability</b>	PVC free
		<b>Operating conditions</b>	-10 °C to 40 °C (14 °F to 104 °F) Humidity 10–85% RH (non-condensing)
		<b>Storage conditions</b>	-40 °C to 70 °C (-40 °F to 158 °F)
		<b>Approvals</b>	<b>Safety</b> IEC/EN 62368-1 <b>Environment</b> IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27
		<b>Dimensions</b>	Height: 23.5 mm (0.9 in) ø 111.5 mm (4.4 in)
		<b>Weight</b>	76 g (0.17 lb)
		<b>Included accessories</b>	Installation guide, mounting screws, UNC mounting screw, locking screws
		<b>Warranty</b>	Axis 3-year warranty, see <a href="http://www.axis.com/warranty">www.axis.com/warranty</a>

Environmental responsibility:

[www.axis.com/environmental-responsibility](http://www.axis.com/environmental-responsibility)