



8531HD

IKALL HD SINGLE-FAMILY KIT W/ SLAVE GW+ICONA. VIP



The kit consists of 1 external unit for ViP kit art. 4894HIM, 1 power supply unit art. 1441B, 1 slave gateway art. 1456S, 1 Icona monitor art. 6602WK, 1 flush-mounted box art. 6117, 1 wall bracket art. 6620. The kit is pre-programmed and ready to use, except for configuration of the gateway art. 1456S, which needs to be carried out via an internal web server. The kit can be expanded with other products in the ViP catalogue. Compatible with H.264 video format.

AWARDS





8531HD

IKALL HD SINGLE-FAMILY KIT W/ SLAVE GW+ICONA. VIP

KIT PRODUCT



4894HIM

External unit for ViP kit - Ikall Metal H264

Single-family video door entry external unit for ViP system with Ikall Metal entrance panel. The kit comprises: 1 flush-mounted box Art. 3110/1, 1 silver coloured frame Art. 3311/1S, 1 module with 1 button art. 33411M and 1 colour audio/video unit Art. 4682HKD. The external unit is coded with ViP address 100 and the button on module Art. 33411M sends the call to ViP address 1. Compatible with H264 video format

MAIN FEATURES - 4894HIM

Audio/video system:	Yes
Flush-mounted:	Yes
Type of sensor:	1/3" CCD
Lens size (inch):	0.14
Minimum color lighting (lux):	0.23
Video resolution (H x V - pixel):	
Video encoding:	H.264
Power supply:	33VDC
Microphone volume control:	Yes
Loudspeaker volume control:	Yes
Operating temperature (°F):	-13 ÷ 131
IP protection rating (IP code):	IP54



6602WK

ICONA MONITOR, VIP KIT H264

Flush-mounted (on box art. 6117) or surface-mounted (with bracket art. 6620) colour monitor with 4.3" / 16:9 touch screen, full-duplex audio. Allows adjustment of backlighting intensity, contrast, audio volume and ringtone volume. Equipped as standard with sensitive touch controls for lock-release, audio activation, self-ignition, privacy service and 3 other controls for programmable functions, door open and new message indicator LEDs. Standard floor door call and call repetition management, with alarm and panic inputs and micro-SD card slot. You can customise the ringtone and video memory function with an absent message. Can also be used on standard PoE systems. Dimensions 5.61"x5.79"x0.91". Compatible with H.264 video format.

GENERAL DATA - 6602WK

Product height (inch):	5.79
Product width (inch):	5.61
Product depth (inch):	0.91
Product weight (oz):	1.1
Product color:	White RAL9003, base grey RAL7001
Material:	ABS, Glass
Flush mounting:	Yes, with a dedicated accessory
Wall mounting:	Yes, with a dedicated accessory
Desk base-mounted:	Yes, with a dedicated accessory

The technical specifications are subject to variations without warning.



8531HD

IKALL HD SINGLE-FAMILY KIT W/ SLAVE GW+ICONA. VIP

GENERAL DATA - 6602WK



1456S

APARTMENT SLAVE GATEWAY FOR VIP SYSTEM

Apartment gateway in slave version (requires presence of a door entry monitor). Allows the operation of door entry monitor system via tablets and smartphones using the Comelit VIP App, which can be downloaded free of charge. This function can be used locally via a Wi-Fi network or on portable devices using 3G (or higher) networks; automatic switching between Wi-Fi and 3G networks according to availability. In all cases, the gateway should be connected to an ASDL router or another device guaranteeing local Wi-Fi and mobile 3G connectivity. Depending on bandwidth limitations, the gateway can serve up to 15 appliances (including door entry monitors, smartphones, tablets and PCs) with 4 simultaneous audio/video streams. It also allows "intercom" communication between all of the 15 devices served. The gateway is equipped with 1 Ethernet port for ViP system riser input, 1 PoE port, 2 PoE ports (can be set to non-PoE) and 1 non-PoE port. It is also equipped with an input for the power supply. Dimensions: 70x90x62 mm (4 DIN modules).

MAIN FEATURES - 1456S

Height (inch):	2.76
Width (inch):	3.54
Depth (inch):	2.44
Operating temperature (°F):	41 ÷ 104
RH max operating humidity (%):	25 ÷ 75
DIN rail mounted:	Yes
DIN modules (no.):	4



1441B

30W VIP SYSTEM POWER SUPPLY UNIT

Power supply unit with 110Vac/240Vac input and 48Vdc output. 30W power. DIN bar power supply unit (4 DIN modules). Dimensions: 72x93x56mm

MAIN FEATURES - 1441B

Supply voltage (VAC):	110÷240
Number of DIN modules:	4



8531HD

IKALL HD SINGLE-FAMILY KIT W/ SLAVE GW+ICONA. VIP

KIT PRODUCT



6117

FLUSH-MOUNTED BOX FOR PLANUX, SMART, ICONA MONITORS

The accessory can be used for the tilt-adjustment fitting of art. 6122. Dimensions: 132X132X50 mm.

MAIN FEATURES - 6117

Height (inch):	5.2
Width (inch):	5.2
Depth (inch):	1.97



6620

WALL BRACKET FOR ICONA MONITOR

Wall bracket for Icona monitor. Colour: White. Dimensions: 136.6x141.6x13.8mm.

MAIN FEATURES - 6620

Height (inch):	5.57
Width (inch):	5.38
Depth (inch):	0.54
Weight (oz):	0.09



8531HD

IKALL HD SINGLE-FAMILY KIT W/ SLAVE GW+ICONA. VIP

ACCESSORIES



4894HIM

External unit for ViP kit - Ikall Metal H264

Single-family video door entry external unit for ViP system with Ikall Metal entrance panel. The kit comprises: 1 flush-mounted box Art. 3110/1, 1 silver coloured frame Art. 3311/1S, 1 module with 1 button art. 33411M and 1 colour audio/video unit Art. 4682HKD. The external unit is coded with ViP address 100 and the button on module Art. 33411M sends the call to ViP address 1. Compatible with H264 video format



6602WK

ICONA MONITOR, VIP KIT H264

Flush-mounted (on box art. 6117) or surface-mounted (with bracket art. 6620) colour monitor with 4.3" / 16:9 touch screen, full-duplex audio. Allows adjustment of backlighting intensity, contrast, audio volume and ringtone volume. Equipped as standard with sensitive touch controls for lock-release, audio activation, self-ignition, privacy service and 3 other controls for programmable functions, door open and new message indicator LEDs. Standard floor door call and call repetition management, with alarm and panic inputs and micro-SD card slot. You can customise the ringtone and video memory function with an absent message. Can also be used on standard PoE systems. Dimensions 5.61"x5.79"x0.91". Compatible with H.264 video format.



1456S

APARTMENT SLAVE GATEWAY FOR VIP SYSTEM

Apartment gateway in slave version (requires presence of a door entry monitor). Allows the operation of door entry monitor system via tablets and smartphones using the Comelit ViP App, which can be downloaded free of charge. This function can be used locally via a Wi-Fi network or on portable devices using 3G (or higher) networks; automatic switching between Wi-Fi and 3G networks according to availability. In all cases, the gateway should be connected to an ASDL router or another device guaranteeing local Wi-Fi and mobile 3G connectivity. Depending on bandwidth limitations, the gateway can serve up to 15 appliances (including door entry monitors, smartphones, tablets and PCs) with 4 simultaneous audio/video streams. It also allows "intercom" communication between all of the 15 devices served. The gateway is equipped with 1 Ethernet port for ViP system riser input, 1 PoE port, 2 PoE ports (can be set to non-PoE) and 1 non-PoE port. It is also equipped with an input for the power supply. Dimensions: 70x90x62 mm (4 DIN modules).



1441B

30W VIP SYSTEM POWER SUPPLY UNIT

Power supply unit with 110Vac/240Vac input and 48Vdc output. 30W power. DIN bar power supply unit (4 DIN modules). Dimensions: 72x93x56mm



6117

FLUSH-MOUNTED BOX FOR PLANUX, SMART, ICONA MONITORS

The accessory can be used for the tilt-adjustment fitting of art. 6122. Dimensions: 132X132X50 mm.



8531HD

IKALL HD SINGLE-FAMILY KIT W/ SLAVE GW+ICONA. VIP

ACCESSORIES



6620

WALL BRACKET FOR ICONA MONITOR

Wall bracket for Icona monitor. Colour: White. Dimensions: 136.6x141.6x13.8mm.