

Description

Altronix T3KAK33F16 kit consists of Trove3 enclosure and TKA3 Keyscan/Altronix door backplane with two (2) 12 or 24VDC @ 6A power supply/chargers, two (2) 8-output fused access power controllers, one (1) 4-output fused power distribution module and one (1) 16VAC transformer. This kit also accommodate various combinations of Keyscan boards for up to sixteen (16) doors in a single enclosure. Trove simplifies board layout and wire management, reduces installation time and labor costs.

dormakaba 



T3KAK33F16

Keyscan boards sold separately

Key Features

- 12/24VDC power supply/chargers.
- Accommodates the following Keyscan controllers:
Up to two (2) CA250B, CA4500B or CA8500B,
up to four (4) OCB8, and two (2) of each DPS15 and CIM.
- Convenient knockout configuration:
 - One (1) single knockout 2.415" (2" Conduit).
 - One (1) double knockout
1.948" (1.5" Conduit) / 1.701" (1.25" Conduit).
 - Sixteen (16) double knockouts
1.362" (1" Conduit) / 1.115" (3/4" Conduit).
- 16 AWG galvanized steel backplane simplifies board layout and wire management.
- Supervision
 - AC Fail
 - Low Battery and Battery Presence
 - Low power shutdown.
- Agency Listings:
 - All Altronix components of this Trove kit are UL Listed sub-assemblies. Please refer to the Sub-Assembly Installation Guides for further information.
 - UL: UL294 - Access Control System.
 - cUL: CAN/ULC - s319-05 - Electronic Access Control Systems.
 - CE European Conformity.
- Enclosure accommodates up to four (4) 12VDC/12AH batteries.
- Lifetime Warranty*.

**Altronix Power Supply/Chargers and Sub-Assemblies only*

Accessories (order separately)



LINQ2

LINQ2 - Network Supervision

Altronix LINQ2 Network Communication Module provides remote supervision, control and monitoring over LAN/WAN

- Remotely reports accurate power diagnostics
- Controls power and resets devices
- Reports system diagnostics via Email



WM5

WM5, WM25, WM100 - Magnetic Cable Tie Mounts

Altronix WM5, WM25, and WM100 are packs of 5, 25 or 100 magnetic cable tie mounts respectively. They accommodate standard zip ties or velcro straps. These are ideal for wire management in our Trove series.



Mounting Magnet

MM4, MM8, MM12, MM24 - Magnetic Mounting Solution

Altronix mounting magnets accommodate screws and nylon standoffs to allow for mounting various boards/ accessories in any metal enclosure or backplane.

Specifications

Power Supplies (eFlow6NB):

Input

Voltage	120VAC, 60Hz, 3.5A max.
Input Fuse	5A/250V.

Outputs

Voltage	Factory set at 24VDC.
Current	6A continuous.
Auxiliary	Class 2 power-limited @ 1A (unswitched).
Other	Overvoltage protection. Filtered and regulated.

Battery Backup *(not included)*

Type	Sealed lead acid or gel type.
Fuse Rating	10A/32VDC.
Failover	Upon AC loss, instantaneous.

Fire Alarm Disconnect

Supervised	Latching or non-latching.
EOL	10K Resistor.

Supervision

AC Failure	Form "C" contacts.
Battery	Form "C" contacts.

Low DC Power Shutdown

Shuts down DC output terminals if battery voltage drops below 70-75% for 24V units. Prevents deep battery discharge.

Indicators (LED)

Input	120VAC is present.
DC Output	Powered.
Battery	Discharged or not connected.

Transformer (T16175):

Input

Voltage	115VAC, 50/60Hz, 1.6A.
---------	------------------------

Output

Voltage	16VAC/175VA. 11A supply current.
---------	----------------------------------

Power Distribution Module (PD4UL):

Input

Voltage	16VAC from T16175.
---------	--------------------

Outputs

Voltage	16VAC.
Four (4) fuse protected outputs. 3.5A per output max.	
Output Fuses	3.5A/250V.

Indicators (LED)

Green LED	AC Output.
-----------	------------

Two (2) Access Power Controllers (ACM8):

Input

Voltage	24VDC from eFlow6NB.
Input Fuse	10A/250V.

Outputs

Voltage	24VDC.
Eight (8) independently controlled fused outputs:	
a) Fail-Safe and/or Fail-Secure power outputs.	
Form "C" Relays rated 28VAC or VDC @ 2.5A.	
b) Auxiliary power outputs (unswitched).	
c) Any combination of the above.	

Output Fuses	3.5A/250V.
--------------	------------

Indicators (LED)

Red LEDs	Outputs are triggered (relays energized).
Green LED	FACP disconnect is triggered.

T3HWK75F16 Kit:

Agency Listings

CE	European Conformity.
----	----------------------

Physical and Environmental

Dimensions (H x W x D)	36.12" x 30.12" x 7.06" (917.5 mm x 768.1 mm x 179.3 mm).
------------------------	---

Weight (approx.)

Product	85 lb. (38.6 kg).
Shipping	92 lb. (41.73 kg).

Temperature

Operating	0°C to 50°C (32°F to 122°F).
Storage	-20°C to 70°C (-4°F to 158°F).

Relative Humidity	85% +/-5%.
-------------------	------------

BTU/Hr (approx.):	152 BTU/Hr.
-------------------	-------------

Access Controller Position Chart for the Following Models:

Keyscan	Pem Mounting
CA250B, CA4500B, CA8500B	Ⓐ
OCB8	Ⓑ
DPS15	Ⓒ
CIM	Ⓓ



