

# Product Specifications




## Flip Toggle Kit 1/4" W/Screws (25 pack)

Part number FTG14B25

Category number 4740

UPC 781002857594

The Flip Toggle Anchor is a single piece, nylon body anchor with a metal tilting head ideal for use in drywall, plaster and hollow wall concrete blocks. It's unique tilting mechanism ensures a trouble-free installation that yields twice the strength of a regular toggle bolt of the same bolt diameter.



### Physical Characteristics

Anchor Type	Flip Toggle
Head Type	Pan
Screw Size	1/4"-20 x 2-1/2"
Anchor Diameter	1/4"
Thread Pitch/Thread Per Inch	1/4"-20
Number of Pieces	25

### Packaging Details

Kit Contains	(25) Flip Toggle Anchors, (25) 1/4"-20 x 2-1/2" Pan Phillips/Slotted Machine Screw
Standard Qty	1
Master Qty	5
Price Per	1
Package Length	2.38
Package Width	6.13
Package Height	10.75
Net Weight	1.64
Package Weight	1.64

### Performance Data

Safe Tension Load	1/2" Drywall: 74lbs, 5/8" Drywall: 120lbs, Hollow Concrete Block: 535lb
Shear Strength	1/2" Drywall: 274lbs, 5/8" Drywall: 418lbs, Hollow Concrete Block: 870lbs
Safe Shear Load	1/2" Drywall: 137lbs, 5/8" Drywall: 209lbs, Hollow Concrete Block: 600lb
Grip Range	1/2" to 2-1/8"
Hole Diameter	1/2"
Applications	Drywall Hollow Block Walls and Ceilings
Special Features	Twice as Strong as Toggle Bolt, Fast and Easy Installation, Suitable for Overhead Applications, One Strap Design, Only Requires 1/2" Hole, Used with Any Bolt Length up to 3-3/4"

### Certifications

RoHS Compliant	Yes
----------------	-----