



5853

Wireless Glassbreak Detector

The Honeywell Home 5853 Wireless Glassbreak Detector offers uncompromised performance and unmatched false alarm immunity. The FlexCore™ signal processor utilizes an Application Specific Integrated Circuit (ASIC)—processing sound data in parallel rather than sequentially. This permits sound frequency, duration and amplitude to be analyzed 50% faster to minimize false alarms while maintaining the highest possible level of detection.

The 5853 can be mounted on any wall or ceiling within a 25' range, with no minimum range limitation. The LEDs indicate test mode, alarms and trouble conditions. It is compatible with all 5800 Series wireless devices.



FEATURES AND BENEFITS

- Test mode can be activated remotely with FG-701 Tester
- Four selectable sensitivity settings (Max, Medium, Low and Lowest)
- FlexCore signal processor
- Senses the sound of a variety of glass (tempered, wired, laminate, ordinary plate, etc.)
- Sleek design with front and back case tamper
- Ten year battery life with easily replaceable batteries
- Transmits supervisory, low battery and tamper messages to control panel

SPECIFICATIONS

Dimensions: 4.95" H x 3.09" W x 1.1" D

Range:

25' (7.6 meters) maximum from farthest protected glass
No minimum range

Power: Two 3V Batteries (included)
Replace only with ADEMCO # 466, Panasonic® CR123A, Sanyo® CR123A, Duracell® DL123A, or Varta CR123A (Lithium Manganese Dioxide)

Operating Temperature: 14°F – 122°F (-10°C to 50°C)

ORDERING

5853

Wireless Glassbreak Detector



Resideo Technologies, Inc.

2 Corporate Center Drive, Suite 100
P.O. Box 9040
Melville, NY 11747
1-800-645-7492
resideo.com

For more information

security.honeywellhome.com/hsc

L/5853D/D | 06/19
© 2019 Resideo Technologies, Inc.
This product is manufactured by Resideo and its affiliates. The Honeywell Home trademark is used under license from Honeywell International Inc. All rights reserved.