

### ELK-1250 12V, 5 Ah

#### FEATURES

- Valve regulated, non-spillable construction
- UL recognized component
- Two year over-the-counter warranty

#### APPLICATIONS

- Back-up battery for security alarm systems, fire alarm systems and access control systems
- Emergency lights
- Lighted exit signs
- Uninterruptible power supplies
- Other general purpose use



UL Recognized Component




97% Recyclable

#### SPECIFICATIONS


<b>Nominal Voltage</b>	12 Volts
<b>Rated Capacity</b>	5 Ah (20 hour rate)
<b>Nominal Capacity (77°F, 25°C)</b>	5 Ah
20 hour rate (0.25A)	5 Ah
10 hour rate (.46A)	4.6 Ah
5 hour rate (.81 A)	4.05 Ah
1 hour rate (2.71 A)	2.71 Ah
<b>Operating Temperature Range</b>	
Storage (in fully charged condition)	-20°C (-4°F) to 60°C (140°F)
Charge	-15°C (5°F) to 50°C (122°F)
Discharge	-20°C (-4°F) to 60°C (140°F)
	Note: Prolonged exposure to extreme temperatures can have long term effects on battery performance
<b>Charge Constant Voltage</b>	14.4V - 14.8V at 77°F (25°C)
Cycle	Initial Charging Current 1.5A Max
Standby	13.5V - 13.8V at 77°F (25°C)
<b>Weight (Approximate)</b>	3.59 lbs (1.63 kg)
<b>Terminals</b>	F1 Faston Tab (.187")

#### DIMENSIONS



Length	3.54" (90 mm)	Case Height	3.94" (100 mm)
Width	2.76" (70 mm)	Total Height	4.17" (106 mm)

#### CAPACITY RETENTION CHARACTERISTICS



#### DISCHARGE CHARACTERISTICS (68°F, 20°C)

