



PRODUCT SPEC SHEET  
R2-5MPBLMTRZ

# 5MP IP IR Motorized Bullet

2560x1920 TRUE DAY/NIGHT



The R2-5MPBLMTRZ is a 5MP (2560 x 1920) IP67 rated bullet camera constructed with a 2.7-13.5mm lens and provides HD Image quality.

## OPTIONAL SERVICES\*

Integrate with Capture Cloud Service, powered by Eagle Eye\*

Connect with Capture Remote Monitoring Service (R2-B12SUBK)\*

*\*Require monthly/annual subscriptions*

## FEATURES

- 2.7-13.5MM LENS
- IR DISTANCE: 40M/131FT
- SUPPORTS MICRO SD CARD, UP TO 256GB
- TRUE WDR
- ONVIF CONFORMANCE
- IP67
- POE/12VDC
- WARRANTY: 36 MONTHS
- PART #: R2-5MPBLMTRZ
- UPC: 840049305298
- LENGTH: 9.13"
- WIDTH: 3.15"
- HEIGHT: 3.15"
- WEIGHT: 1.79 LB



FOR MORE INFORMATION, CONTACT YOUR ADI SALES PERSON.

# Capture

▶▶▶▶▶ advance

PRODUCT SPEC SHEET  
R2-5MPBLMTRZ

## Caméra Ogivale Motorisée IP IR 5 Mpx



JOUR/NUIT AUTHENTIQUE 2560 x 1920

Le modèle R2-5MPBLMTRZ est un camera ogivale 5 Mpx (2560 x 1920) certifiée IP67 dotée d'un objectif de 2,7 - 13,5 mm et offrant une qualité d'image HD.

**SERVICES EN OPTION\***

**Intégrez-vous à Capture Cloud Service, optimisé par Eagle Eye.\***

**Connexion aux services de surveillance à distance de Capture (R2-B12SUBK)\***

*\*Nécessite un abonnement mensuel ou annuel*

### FEATURES

- OBJECTIF DE 2,7 - 13,5 MM
- DISTANCE (IR) : 40 M/131 PI
- PRISE EN CHARGE DES CARTES MICRO SD JUSQU'À 256 GO
- PLAGES DYNAMIQUES ÉTENDUES
- CONFORMITÉ ONVIF
- IP67
- POE/12 VCC
- GARANTIE : 36 MOIS
- PART #: R2-5MPBLMTRZ
- UPC: 840049305298
- LENGTH: 9.13"
- WIDTH: 3.15"
- HEIGHT: 3.15"
- WEIGHT: 1.79 LB



FOR MORE INFORMATION, CONTACT YOUR ADI SALES PERSON.

#### CAMERA

<b>IMAGE SENSOR</b>	1/2.8" PROGRESSIVE SCAN CMOS
<b>EFFECTIVE PIXELS</b>	2560(H)×1920(V)
<b>ELECTRONIC SHUTTER</b>	AUTO/MANUAL, 1/5 - 1/20,000S
<b>MIN. ILLUMINATION</b>	COLOR: 0.03 LUX @ (F1.6, AGC ON) , B/W: 0 LUX @ (IR LED ON)
<b>S/N RATIO</b>	55DB
<b>DAY/NIGHT</b>	AUTO(ICR)
<b>WIDE DYNAMIC RANGE</b>	TRUE WDR
<b>IR RANGE</b>	UP TO 40 M (131 FT)
<b>IR ON/OFF CONTROL</b>	AUTO/MANUAL
<b>PAN/TILT/ROTATION RANGE</b>	PAN: 0° - 360°, TILT: 0° - 90°, ROTATION: 0° - 360°

#### LENS

<b>LENS TYPE</b>	MOTORIZED
<b>IRIS</b>	FIXED IRIS
<b>FOCAL LENGTH</b>	2.7 - 13.5 MM
<b>F NUMBER</b>	F1.6
<b>ANGLE OF VIEW</b>	H: 87.5° - 26°, V: 64.8° - 19.9°

#### VIDEO

<b>MAX. RESOLUTION</b>	5MP (2560×1920)
<b>STREAMING CAPABILITY</b>	3 STREAMS
<b>STREAM/FRAME RATE</b>	STREAM1: 2560×1920, 2592×1520, 1920×1080, 1280×720 @ 25/30FPS STREAM2: D1, VGA, CIF @ 25/30FPS STREAM3: VGA, CIF, QVGA @25/30FPS
<b>BIT RATE CONTROL</b>	CBR/VBR
<b>BIT RATE</b>	STREAM1: 200KBPS-12MBPS STREAM2: 100KBPS-6MBPS STREAM3: 100KBPS-3MBPS
<b>IMAGE ENHANCEMENT</b>	HLC / BLC / DEFOG / WDR
<b>WHITE BALANCE</b>	AUTO
<b>GAIN CONTROL</b>	AUTO/MANUAL
<b>NOISE REDUCTION</b>	2D/3D DNR
<b>AISLE MODE</b>	SUPPORTED
<b>SMART IR</b>	SUPPORTED
<b>MIRROR</b>	SUPPORTED
<b>REGION OF INTEREST</b>	OFF/ON (8 ZONE, RECTANGLE)
<b>MOTION DETECTION</b>	SUPPORTED
<b>PRIVACY MASKING</b>	SUPPORTED

#### SMART FUNCTION

<b>SMART FUNCTION</b>	SUPPORTS FACE, HUMAN, VEHICLE DETECTION
<b>INTELLIGENT DETECTION</b>	PERIMETER, SINGLE VIRTUAL FENCE, DOUBLE VIRTUAL FENCES, LOITER, PEOPLE COUNTING

#### AUDIO

<b>COMPRESSION</b>	G.711, RAW_PCM
<b>BIT RATE</b>	8KBPS, 16KPS, 64KBPS

#### NETWORK

<b>PROTOCOLS</b>	IPV4/IPV6, 802.1X, HTTP, HTTPS, TCP/IP, UDP/IP, RTSP, DHCP, NTP, RTCP/RTSP, PPPoE, SMTP, DNS, UPNP, FTP, ARP, SNMP, TLS/SSL
<b>INTEROPERABILITY</b>	ONVIF, SDK, CGI
<b>STREAMING METHOD</b>	UNICAST
<b>MAX. USER ACCESS</b>	10 USERS
<b>WEB VIEWER</b>	<IE11, CHROME, FIREFOX, MICROSOFT EDGE
<b>MANAGEMENT SOFTWARE</b>	CAPTURE ADV

#### INTERFACE

<b>ETHERNET</b>	1 ETHERNET (10/100 BASE-T) RJ-45 CONNECTOR
<b>AUDIO</b>	1CH INPUT, 1CH OUTPUT
<b>ALARM</b>	1CH INPUT, 1CH OUTPUT
<b>RESET BUTTON</b>	SUPPORTED
<b>STORAGE</b>	BUILT-IN MICRO SD SLOT, UP TO 256G

#### ELECTRICAL

<b>POWER SUPPLY</b>	DC12V/POE (IEEE 802.3AF)
<b>POWER CONSUMPTION</b>	MAX 8.5 W
<b>OPERATING TEMPERATURE</b>	-40°C - 55°C (-40°F - 131°F)
<b>OPERATING HUMIDITY</b>	LESS THAN 90% RH
<b>INGRESS PROTECTION</b>	IP67
<b>CERTIFICATIONS</b>	CE/FCC
<b>CASING</b>	METAL
<b>DIMENSIONS</b>	232 × 80 × 80MM (9.13" × 3.15" × 3.15")
<b>NET WEIGHT</b>	0.81 KG (1.79 LB)

**FOR MORE INFORMATION,  
CONTACT YOUR ADI SALES PERSON.**