



## LED-2155HD

Commercial-grade, LED-backlit, LCD monitor displays Full HD without downscaling. This all-purpose model is designed for use in 24/7 environments and it is ideal for all video and computing applications.

### Benefits

- LED backlight: brighter picture using less power
- Displays Full HD signals (1920 x 1080) with no downscaling
- 3D Comb Filter displays clearer image
- Widescreen (16:9) native aspect ratio
- Built-in removable deskstand
- Built-in speakers

### Specifications

<b>Mount</b>	VESA 100 x 100mm; Removable Deskstand
<b>Case</b>	Durable ABS Plastic
<b>HD Compatible</b>	Displays 1080i/p
<b>Native Aspect Ratio</b>	16:9
<b>Visible Screen Size (WH)</b>	18.03" x 10.14" / 457.92 x 257.58mm
<b>Resolution</b>	1920 x 1080 (Full HD)
<b>Brightness Rating</b>	250 cd/m <sup>2</sup> (Nit)
<b>Contrast Ratio</b>	1000:1
<b>Back Light</b>	LED
<b>Dot Pitch</b>	0.248 x 0.248mm
<b>Color Depth</b>	16.7 million
<b>Number of Pixels</b>	2,073,600
<b>Response Time</b>	5ms (Rising/Falling)
<b>Audio Power / Speakers</b>	x2 Speakers at 5 Watts
<b>Viewing Angle (L/R/T/B)</b>	85/85/85/85 degrees
<b>Digital Signal Processing</b>	3D Comb Filter
<b>Operating Temp</b>	32 ~ 104°F / 0 ~ 40°C
<b>Humidity</b>	10% ~ 95%
<b>Power Requirements</b>	100 ~ 240 V; 50/60 Hz
<b>Power Consumption</b>	< 25 Watt (Active); < 0.5 Watt (Stand-by)
<b>VGA</b>	x1 Input
<b>HDMI</b>	x1 Input
<b>Composite</b>	x1 BNC Input; x1 BNC Output
<b>Audio</b>	x1 3.5mm Input; x1 3.5mm Output
<b>Power</b>	120 Volts
<b>Dimensions w/ Deskstand</b>	19.4" x 14.4" x 6.4" / 491.6 x 365.4 x 163.7mm
<b>Dimensions</b>	19.4" x 11.9" x 2.1" / 491.6 x 301.1 x 53.5mm
<b>Weight</b>	Net: 8.38 lbs / 3.8 kg

Product specifications subject to change.