

Indoor

Enhanced UTP

Copper

Product Highlights

- REACH & RoHS 2 compliant
- Made in U.S.A.
- UL Verified
- Low Smoke Plenum construction
- Guaranteed minimum performance
- Enhanced performance beyond TIA Standard
- Tested from 1 to 660 MHz

TIA Parameter	Guaranteed Headroom
NEXT loss	+5 dB
PSNEXT loss	+5 dB
ACRF	+6 dB
PSACRF	+6 dB

Packaging

- 1,000 feet (305 m)
- Reverse sequential footage markings standard on each 1,000 foot package
- Unit/pallet: 32 Reels
CMP Carton Weight (lbs): 29.04
CMP Product Weight (lbs): 25.74
*weight may vary, call for CMR information

Options

- CMP-50 rated cables available

Applications

- Including:
HDBase-T A & B
5 Gigabit Ethernet (IEEE 802.3bz)
2.5 Gigabit Ethernet (IEEE 802.3bz)
Gigabit Ethernet (IEEE 802.3ab)
100 Mbps Ethernet (IEEE 802.3u)
1000 Mbps ATM
622 Mbps ATM
15W PoE (IEEE 802.3af)
30W PoE+ (IEEE 802.3at)
60W PoE++ (IEEE 802.3bt Type 3)
100W PoE++ (IEEE 802.3bt Type 4)

Temp. Range

- Storage Temperature
-40°C to +60°C
(-40°F to +140°F)
- Installation Temperature
0°C to +60°C
(+32°F to +140°F)
- Operation Temperature
-20°C to +75°C
(-4°F to +167°F)

Premium UTP (Plenum)

c(UL)us Listed Type CMP (NFPA 262), CSA Type FT6

PART #	# OF PAIRS	CALCULATED CABLE O.D.		CABLE WEIGHT	
		inches	mm	lbs/1000 ft	kg/305 m
30183-8-XXY	4	0.20	5.1	25.74	11.68

Premium UTP (Riser)

c(UL)us Listed Type CMR (UL 1666), CSA Type FT4

PART #	# OF PAIRS	CALCULATED CABLE O.D.		CABLE WEIGHT	
		inches	mm	lbs/1000 ft	kg/305 m
30212-8-XXY	4	0.215	6.22	26.93	12.22

Building a Part Number

Base Part Number Ex.	No. of Conductors	Jacket Color	Reel Type
30183	8	XX	Y


Jacket Colors (XX):

Black (BK); Blue (BL); Brown (BR); Gray (GA); Green (GR); Red (RD); White (WH); Violet (VI); Yellow (YE)

Reel Type (Y):

Reel (2); Reels

Features



3D Image represents the CMP Configuration

DIELECTRIC MATERIALS

PLENUM

Primary Insulation: Plenum-rated fluoropolymer
Overall Jacket: Low-smoke, flame-retardant thermoplastic
Star Filler: Plenum-rated polymer

RISER

Primary Insulation: Polyolefin
Overall Jacket: Flame-retardant Thermoplastic
Star Filler: Flame-retardant Thermoplastic

Hitachi Cable America reserves the right to revise any specifications.

Cat 6 Premium

Transmission Specifications

ANSI/TIA-568.2-D Category 6 Verified
ISO/IEC 11801, 2nd ed. Class E Compliant

Freq. (MHz)	Ins. Loss		NEXT		PSNEXT		ACR		PSACR		ACRF		PSACRF		Return Loss	
	Std.	Max.	Std.	Min.	Std.	Min.	Cal.	Min.	Cal.	Min.	Std.	Min.	Std.	Min.	Std.	Min.
1	2.0	2.0														20.0
4	3.8	3.8														23.0
8	5.3	5.3														24.5
10	6.0	6.0														25.0
16	7.6	7.6														25.0
31.25																23.6
62.50																21.5
100																20.1
155																18.8
200									8.8							18.0
250							5.5		3.5	8.5						17.3
300*	-	-	-	-	-	-	0.7	5.7	-	3.7	-	-	-	-	-	16.8
350*	-	-	-	-	-	-	-	1.4	-	-	-	-	-	-	-	16.3
400*	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	15.9
500*	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	15.2
555*	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	14.9
660*	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	14.4

*Frequencies beyond the TIA and ISO requirements are for information only. All values are dB/100m.



Copper

Photo is for representation purposes only.



Electrical Characteristics

Input Impedance:	100 ± 15Ω (1.0 to 100 MHz) 100 ± 20Ω (101 to 160 MHz) 100 ± 25Ω (161 to 250 MHz)
Maximum Resistance Unbalance:	3%
Maximum Capacitance Unbalance:	330 pF/100 meters
Maximum Delay Skew:	35 ns/100 meters (CMP) 45 ns/100 meters (CMR)
Nominal Velocity Of Propagation (Nvp):	70%, Plenum 68%, Riser

Cable Ampacity Chart							
Bundle Size	1	2-7	8-19	20-37	38-61	62-91	92-192
Cable Temp	75°C	75°C	75°C	75°C	75°C	75°C	75°C
23 AWG	2.5	1.5	1.1	0.8	0.7	0.7	0.5

The table above is derived from the one approved by the National Fire Protection Agency and used in the National Electrical Code, NFPA-70. The complete table can be found in sections 725.144 and 800 Communication Circuits of the code. The table identifies the ampacity of each conductor (in amperes) in a 4-pair Class 2 or Class 3 data cable. Ambient temperature used for development of the table is 30°C (86° F) with all conductors in all cables carrying current. The table is based on 60°C (140°F), 75°C (167°F) and 90°C (194°F) rated cables. All cable temps are operational temp ratings. Cables with temp ratings above 90c would deliver additional power handling capacity.