

LED-1908HDL - Front



LED-1908HDL

This LED-backlit flush mount monitor features the latest technology with enhanced picture clarity and sharpness for both analog and digital video signals.

Benefits

- Analog video is very clear with no detail loss
- Displays 1080i/p digital video
- 3D Comb Filter for better picture quality
- High contrast ratio for better picture definition
- Durable metal case

Related Products

- LED-1908HD
- LED-1908HDR
- LED-1908HDVB
- LED-1708HD
- LED-1708HDL
- LED-1708HDR

Specifications	
Mount	Flush mount
HD Compatible	Yes
Anti Glare Coating	Yes
V Chip/Closed Caption	n/a
Selectable Color Temp.	Yes
Case	Durable Metal
Built-in Power Supply	No
IR Remote Control	No
180° Rotation Display	No
Native Aspect Ratio	5:4
Visible Screen Size (WH)	376.3 x 301 / 14.8" x 11.8"
Resolution	1280(H) x 1024(V) dots
Brightness Rating	300 cd/m ²
Contrast Ratio	10,000:1
Back Light	LED
PC Compatibility	Yes
Dot Pitch	0.294(H) x 0.294(V)
Colors	16.7 M
Number of Pixels	1,310,720
Response Time	5 ms
Audio Power / Speakers	1.5W x 2
Viewing Angle (L/R/T/B)	170/170/160/160 degrees
Pixel Configuration	Stripe
Input Signal	Analog and Digital audio/video
Input Signal Level	1.0V P-P (positive) 75 Ohm
3D Comb Filter	Yes
Removable Desk Stand	n/a
Dimensions w/ Deskstand	n/a
Dimensions w/o Deskstand	465.5x 409 x 72mm/18.4" x 16.1" x 2.9"
Installer's Cut Out	16.4" x 14.5"
Operating Temp/Humidity	32 ~ 104°F / 0 ~ 40°C, 10% ~ 90% humidity
Power Requirements	DC 12V (AC100~240)[50/60]
Power Consumption	15W Max
Component	No
Composite	BNC IN/OUT x 2
S-Video	No
PC	VGA in/out 15 pin D-sub
HDMI / DVI / RS-232	Yes/No/No
Audio	RCA audio inputs, PC stereo in
Power	2.1mm DC IN jack
Weight	Net 5.4Kgs/11.8 lbs, Gross 7.9Kg/17.3 lbs.
GSA	Yes