



## LED-1906HDMTL

High-definition, LED-backlit, flush mount monitor with TV tuner that is versatile and effective for use in any commercial video application.

### Benefits

- Displays HD signals (1080i/p and 720p)
- 3D + 3D image processing with digital noise reduction
- Built-in ATSC / Clear QAM Tuner
- Built-in speakers
- IR remote control

### Related Products

- LCD-1906HDMTR: Rack-mount version
- LCD-1906HDT: Wall-mount version with removable deskstand

Specifications	
Mount	Flush Mount
HD Compatible	Yes
Anti Glare Coating	Yes
Screen Panel	18.5" TFT Active Matrix
Case	Durable Metal
IR Remote Control	Yes
Native Aspect Ratio	16:9
Visible Screen Size (WH)	16.1" x 9.1" / 409.8 x 230.4mm
Resolution	1366(H) x 768(V)
Brightness Rating	230 cd/m <sup>2</sup> (Nit)
Contrast Ratio	1000:1
Back Light	LED (30K)
Dot Pitch	0.30(H) x 0.30(V)mm
Color Depth	16.7M
Number of Pixels	1,049,088
Response Time	5ms (Rising/Falling)
Audio Power / Speakers	8 Ohm, 2 Speakers x 2 Watts
Viewing Angle (L/R/T/B)	85/85/80/80 degrees
3D Comb Filter	Yes
Dimensions	20" x 14.5" x 1.93" / 508.5 x 369 x 49mm
Operating Temp	6 ~ 104°F / -14 ~ 40°C
Humidity	10% ~ 90%
Power Requirements	100 ~ 240 VAC; 50/60 Hz
Power Consumption	< 25 Watts (Max); < 0.5 Watts (Stand-by)
Component	x1 RCA YPbPr Input
Composite	x2 RCA Inputs; x1 RCA Output
PC	x1 VGA 15-pin D-sub Input
HDMI	x3 Inputs
TV (RF)	x1 F (Coax) Input
Audio	x1 RCA L/R Output; x1 3.5mm PC Input
Power	x1 AC Input
Weight	Net: 8 lbs / 3.6 kg; Gross: 11.2 lbs / 5.1 kg

Specifications subject to change.