



HDMI EXTENDER BI-DIRECTIONAL POC

0E-HDMIEX4KC



0E-HDMIEX4KC HAS CAPABILITIES TO TRANSMIT 4K@60HZ (CHROMA SUB-SAMPLING 4:4:4 8-BIT) UHD VIDEO, HD AUDIO AND IR CONTROL SIGNAL.

SPECIFICATIONS:

Technical

- Input: 1 x HDMI IN
- Output: 1 x HDMI OUT
- Input/Output Signal Type: HDMI 2.0b, HDCP 2.2
- Resolution Supported:
Up to 4096x2160@60Hz, including 4K@60Hz/4K@30Hz/1080P/1080i/720P
- Maximum Data Rate: 18Gbps
- Maximum Pixel Clock: 600MHz
- Transmission Distance:
Cat 5e cable - 1080P@60Hz: up to 50m/164ft;
4K@30Hz: up to 40m/131ft.
Cat 6/6a/7 cable - 1080P@60Hz: up to 50m/164ft;
4K@30Hz: up to 40m/131ft;
4K@60Hz: 35m/115ft.
Note: T568B straight-through category cables are recommended to use.
- Warranty: 2 years



- PART#: 0E-HDMIEX4KC
- UPC: 840049302440

General

- Operating Temperature:
0°C to 45°C (32°F to 113°F)
- Storage Temperature:
-20°C to 70°C (-4°F to 158°F)
- Humidity:
10% to 90%, non-condensing
- ESD Protection:
±8kV (Air-gap discharge)/
±4kV (Contact discharge)
- Surge Protection: Voltage: ±1 kV
- Power Supply: DC 12V 1A
- Power Consumption (max): 6.48W (Pair, PoC)
- Device Dimension (Transmitter / Receiver):
7.0cm x 1.52cm x 9.0cm/2.76" x 0.60" x 3.54"
- Product Weight (Transmitter/Receiver): 0.2kg/0.44lb

For more information please call 1-833-574-9124
or email AVARRO@adiglobal.com

To learn more about AVARRO products visit
avarro.adiglobaldistribution.us



For more information please call 1-833-574-9124
or email AVARRO@adiglobal.com

To learn more about AVARRO products visit
avarro.adiglobaldistribution.us