

# Catch the **Wi-Fi 6E** wave

with Hubbell's NEXTSPEED ASCENT 6A Cabling System  
and AccelTex Solutions Wireless Accessories



WiFi 6E now supports tri-band data delivery (2.4, 5, and 6GHz). This new milestone provides increased bandwidth and lower latencies. Hubbell's Category 6A cabling system supports up to 10GBASE-T, providing ample bandwidth with the most efficient PoE delivery. Coast through Wi-Fi 6E and be ready for Wi-Fi 7 and beyond with Hubbell's 25-Year Mission Critical® application assurance warranty.

**MAXIMUM BANDWIDTH • SUPERIOR POWER DELIVERY**

## Surface Mount Boxes

Description	1-Port	2-Port
Standard	<b>HSB1xx</b>	<b>HSB2xx</b>
UL Plenum Rated	<b>HSB1xxP</b>	<b>HSB2xxP</b>

xx = Color: **BK** (Black), **EI** (Electric Ivory), **GY** (Gray), **OW** (Office White), **W** (White)



## NEXTSPEED® Ascent Category 6A Reduced Dia. Cable

NVP: Plenum 71%, Riser 66%; 1000ft

Plenum		Riser	
Reel in a Box	Spool	Reel in a Box	Spool
<b>C6ASPDSxx</b>	<b>C6ASPPDSxx</b>	<b>C6ASRDSxx</b>	<b>C6ASPRDSxx</b>

xx = Color: **BK** (Black), **B** (Blue), **GY** (Gray), **GN** (Green), **OR** (Orange), **P** (Purple), **R** (Red), **W** (White), **Y** (Yellow)



## NEXTSPEED® Ascent Category 6A Patch Cords

	Single Pack	24-Piece Bulk Pack
Standard; nominal O.D. 0.290"	<b>HC6Axxyy</b>	<b>HC6Axxyy</b>
Low Diameter; nominal O.D. 0.186"	<b>HCL6Axxyy</b>	<b>HC6LAxxyy</b>

xx = Color: **BK** (Black), **B** (Blue), **GY** (Gray), **GN** (Green), **OR** (Orange), **PK** (Pink), **P** (Purple), **R** (Red), **W** (White), **Y** (Yellow)

yy = Standard Length: **01** (1'), **03** (3'), **05** (5'), **07** (7'), **10** (10'), **15** (15'), **20** (20').  
Made-to-order lengths are available.

## NEXTSPEED® Ascent Category 6A Patch Panels

Format	Width   Inches (mm)	Height   Inches (mm)	Ports	Rack Units	Catalog No.
Straight*	19" (483)	1.75" (45)	24	1	<b>HPJ6A24</b>
		3.50" (89)	48	2	<b>HPJ6A48</b>
Angled**	19" (483)	1.75" (45)	24	1	<b>HPJ6A24A</b>
		3.50" (89)	48	2	<b>HPJ6A48A</b>

\*Versions without cable management bar available as HP6A24E and HP6A48E.

\*\*Angled panel protrudes 4.46" from plane of the rack; one extra inch of space recommended between door & panel.



## AccelTex SOLUTIONS Polycarbonate Lock Box Enclosure

12" X 16" X 4" (304.8 x 406.4 x Indoor/Outdoor)

Product Weight; 4.19 lb Catalog No.

Ship Weight; 4.89 lb **ATS-ENC-12164P-LB**

Color: **W** (White)



## AccelTex SOLUTIONS Dual AP & Quad Antenna Mount

All-Thread Drop Mount

Weight; 16.5 lb (7.48 kg)

Catalog No.

Dimensions; 30.0"x9.50" (795x243.5mm)

**ATS-DRPMNT-DAP-QOP**

Color: **W** (White)

## TIA Guidance TSB-162-A

- Two ports of a minimum of Category 6A performance per AP location

## Specifying Cabling per Wireless Access Point Location

- *Data rate*: Recommended support of 10GBASE-T speeds
- *Current carrying capacity*: Recommended support proposed for PoE levels of at least 49W, and up to 100W
- *Number of ports*: Two to support 10GBASE-T with PoE or to support link aggregation

## NEXTSPEED® Ascent Category 6A Jacks with COBRA-LOCK Termination

Unit of Measure	Catalog No.
Single pack	<b>HJUAXx</b>
Single pack	<b>HJU6Axx</b>
25-pack	<b>HJU6Axx24</b>
Single pack	<b>CB2</b>
Single pack	<b>SCP6A</b>
Single pack	<b>SC6A</b>
Single pack	<b>SP6A</b>
Single pack	<b>SP6A90</b>

xx = Color: **BK** (Black), **B** (Blue), **EI** (Ivory), **GL** (Gold), **GY** (Gray), **GN** (Green), **OW** (Office White), **OR** (Orange), **P** (Purple), **R** (Red), **W** (White), **Y** (Yellow)

