



Product: 2183P ☑

4K UHD Media Cable, 4 Pr #23, F/UTP Flamarrest® Jacket, CMP

Product Description

4 Pair 23 AWG Solid Bare Copper Conductors, FEP Insulation, F/UTP, Helical TC Drain, Ripcord, Flamarrest® Jacket, Plenum CMP-LP (0.6A)

Technical Specifications

Product Overview

| Suitable Applications: | HDBaseT, Full 5-Play, 4K (UHD/DCI), POH, POE |
|------------------------|--|

Construction Details

Conductor

| Element | Number of Element | Size | Stranding | Material |
|---------|-------------------|--------|-----------|------------------|
| Pair(s) | 4 | 23 AWG | Solid | BC - Bare Copper |

Insulation

| Element | Material | Nom. Thickness | Nom. Insulation Diameter | Color Code |
|---------|--------------------------------------|--------------------|--------------------------|-----------------------------|
| Pair(s) | FEP - Fluorinated Ethylene Propylene | 0.010 in (0.25 mm) | 0.0435 in mm | Western Electric (Modified) |

Outer Shield

| Shield Type | Material | Coverage | Drainwire Type | Notes |
|-------------|-------------------------|----------|-------------------|---|
| Таре | Bi-Laminate (Alum+Poly) | 100% | 26 AWG (Solid) TC | Two drain wires applied helically for added flexibility |

Outer Jacket

| | Material | Nom. Thickness | Nom. Diameter | Ripcord |
|---|---------------------------|--------------------|---------------|---------|
| | PVC - Polyvinyl Chloride | 0.018 in (0.46 mm) | 0.270 in | Yes |
| ĺ | Overall Cable Diameter (I | Nominal): 0.270 in | | |

Electrical Characteristics

Electricals

| Nom. Conductor DCR | Nom. Velocity of Prop. | Max. Current |
|--------------------|------------------------|--------------------------------|
| 22.7 Ohm/1000ft | 72% | 3.1 Amps per Conductor at 25°C |

Voltage

UL Voltage Rating

Mechanical Characteristics

Temperature

| UL Temperature | Operating | Installation | Storage |
|----------------|----------------|--------------|----------------|
| 90°C | -20°C to +90°C | 0°C To +75°C | -20°C to +75°C |

Bend Radius

|--|

Standards and Compliance

| Environmental Suitability: | Indoor - Plenum, Indoor, Outdoor | |
|----------------------------------|--|--|
| Flammability / Reaction to Fire: | NFPA 262 (UL 910), FT6 | |
| NEC / UL Compliance: | Article 800, CMP-LP (0.6A), CL3P | |
| CEC / C(UL) Compliance: | CMP | |
| IEEE Compliance: | OE per 802.3af & POE+ 802.3at-2009 | |
| ISO/IEC Compliance: | 11801 ed 2.2 (2011) Class D | |
| European Directive Compliance: | EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE), REACH: 2017-07-10 | |
| APAC Compliance: | hina RoHS II (GB/T 26572-2011) | |
| Other Standard Compliance(s): | C(UL)US CMP 90C OR (UL) CMR-LP (0.6A) OR CL3R-LP (0.6A) OR POH, HDBaseT Recommended Cable | |
| Non-Plenum Number: | 2183R | |

Product Notes

| ١ | Notes: | Values Above 100 MHz are for Engineering Information Only. Print Includes Descending Footage Markings. |
|---|--------|--|
| | | |

History

| Update and Revision: | Revision Number: 0.338 Revision Date: 04-08-2022 |
|----------------------|--|
| | |

Part Numbers

Variants

| Item # | Color | Putup Type | Length | UPC |
|----------------|-------|--------------|----------|--------------|
| 2183P 010A250 | Black | Reel-in-Box | 250 ft | 612825392958 |
| 2183P 0101000 | Black | Reel | 1,000 ft | 612825391678 |
| 2183P 010A1000 | Black | Reel-in-Box | 1,000 ft | 612825391708 |
| 2183P 010Z1000 | Black | ReelTuff Box | 1,000 ft | 612825433231 |
| 2183P D15A1000 | Blue | Reel-in-Box | 1,000 ft | 612825391685 |
| 2183P D15Z1000 | Blue | ReelTuff Box | 1,000 ft | 612825433286 |
| 2183P 009A1000 | White | Reel-in-Box | 1,000 ft | 612825391692 |
| 2183P 009Z1000 | White | ReelTuff Box | 1,000 ft | 612825433187 |

© 2022 Belden, Inc

All Rights Reserved

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.