



Product Overview:

This deceptively simple looking loop acts as a wireless connection to hearing aids equipped with a "T" coil. Listeners hook the loop into their wireless receiver, slip the loop around their neck, and the "T" coil picks up the sound and amplifies the transmitted sound into the ear.

Highlights:

- Use with any hearing aid equipped with a "T" coil
- Use with any Listen's receivers
- The receiver's antenna is built into the headphone cord

Includes:

One (1) LA-166 Neck Loop

| Product Specification: Neck Loop | |
|----------------------------------|---|
| Compliance | |
| Safety | RoHS |
| Standards | IEC 60118-4 |
| Audio | |
| Frequency Response | 20 Hz - 20 kHz |
| Impedance | 12 ohm +/- 15% @ 1 kHz |
| Rated Power Input | 75 mW |
| Max Power Input | 2 W |
| Headset Input Sensitivity | 110 dB +/- 4dB @ 1 kHz, 1 mW |
| Magnetic Field Strength | 100 mA/m 6 inches above loop at 85µW 1kHz input (IEC 60118-4) |
| Loop | |
| Loop Cable Length | 33 in. (84 cm) |
| Interconnections | |

LA-166
Neck Loop

| | |
|------------------------|--|
| Connectors | 3.5 mm Stereo |
| Physical | |
| Cable Length | 22 in. (55 cm) |
| Color | Dark Grey |
| Dimensions (H x W x D) | 1.44 in. x 1.10 in. x 0.59 in. (35 mm x 28 mm x 15 mm) |
| Weight | 1.65 oz. (47 g) |
| Shipping Weight | 1 lb. (0.5 kg) |