



5.0

3 Reviews



5.0

3 Reviews

Need Help?

[Browse All Products](#) | [Active Devices](#) | [USB](#) | [USB Extension Cables and Devices](#) | [USB Active Cables A to B](#)

25ft USB A/B Active Cable (Center Booster Format)

Connect your USB device an incredible 25 feet away (7.62m)!



5.0

3 Reviews

Product # : 38989

Connector 1 : (1) USB-A Male

Connector 2 : (1) USB-B Male

Roll over image to zoom in

2,818 In Stock & ready to ship!



Need it shipped today?

Place your order before the timer runs out!



print share chat

Product Info

Customer Reviews

Questions & Answers

Distributors

Description

Features

Specs

Product Description

This 25ft cable actively buffers the incoming and outgoing signals to ensure compliance with the USB 2.0 specification for electrical and timing minimums. Designed for use with most USB 2.0 or 1.1 devices like some interactive whiteboards, hard drives and printers. Both low and high speed USB devices will function equally well with this extension cable. The active chip is built into the middle of the cable so you can add a 5 meter USB cable when the active cable is used in combination with a USB wall plate.

Product Features

- Extends USB 2.0 signals beyond the five meter length limitation
- Center booster format allows this cable to be easily run through raceway
- Consumes 100mA from the USB port of the computer

WARNING: Cancer and Reproductive Harm www.P65Warnings.ca.gov

Product Specifications

Color :	Black
Length :	25.00 Foot
UPC :	757120389897
Warranty :	1 Year
Vendor :	C2G
Weight :	0.711 LB

- Data Signal Specifications - USB 2.0
- Maximum Data Transfer Rate - 480Mbps
- USB Power Consumed - 100mA

Cable Specifications

Conductor (Qty 1 pair)

- Conductor Type - 28AWG (7/0.120), Tinned Copper
- Colors: (white, green)

Conductor (Qty 2 conductors)

- Conductor Type - 22AWG (7/0.254), Tinned Copper
- Colors - (1) red, (1) black

Physical Characteristics

Connector (Qty 2)

- Connector Type - USB Type A Male
- Contact Plating - 30Ωm Gold Plating
- Insulation - Black PBT

- Voltage Rating - 30V
- Temperature Rating - 80°C
- Hood Material - SR - Molded Black PVC
- Plastic Cover Material - Black ABS
- Plastic Cover Dimension - 78.0 x 28.0 x 18mm
- Weight - 0.346kg

Overall Cable

- Foil Shields - Aluminum Mylar, 100% coverage min.
- Braided Shield - 16/4/0.100, Tinned Copper, 65% coverage min.
- Jacket - PVC, black
- Outer Diameter - 5 ± 0.1mm

Recently Viewed...



Info

- About Us
- Order History
- Where To Buy
- More ▾

Service

- Contact Us
- OEM Solutions
- Tech Support
- More ▾

Resources

- Connector Guides
- ConnectXpress
- Drivers & Manuals
- More ▾

Have A Question?

Get help with [Chat](#)

Call C2G **800.506.9607**



