



12m USB A/B Active Cable

- Overcome the 5m length limitation of USB
- Supports data transfer rates up to 480Mbps
- Standard USB A and USB B connectors
- Active component housed in the middle of the cable.
- No software required

Specifications: 12m USB A/B Active Cable

Signal Specifications:

Data Signal Specifications:	USB 2.0
Maximum Data Transfer Rate:	480Mbps
USB Power Consumed:	100mA

Cable Specifications:

Conductor: (Qty 1 pair)


Conductor Type:	28AWG (7/0.120) Tinned Copper
Colors:	(white, green)

Conductor: (Qty 2 conductors)

Conductor Type:	22AWG (7/0.254) Tinned Copper
Colors:	(1) red, (1) black

Overall Cable:

Foil Shields:	Aluminum Mylar 100% coverage min.
Braided Shield:	16/4/0.100 Tinned Copper 65% coverage min.
Jacket:	PVC black
Outer Diameter:	4.90 ± 0.1mm



Physical Characteristics:

Voltage Rating:	30V
Temperature Rating:	80°C
Hood Material:	SR - Molded Black PVC
Plastic Cover Material:	Black ABS
Plastic Cover Dimension:	57.0 x 28.0 x 17.5mm
Weight:	0.346kg

Connector:

Connector Type:	USB Type A Male
Contact Plating:	30µm Gold Plating
Insulation:	Black PBT

Connector:

Connector Type:	USB Type B Male
Contact Plating:	30µm Gold Plating
Insulation:	Black PBT

Part Number	Description	Weight (lbs)
38998	12m USB A/B Active Cable	0.792

