

Power Cord Adapter, NEMA L5-20R to NEMA 5-20P - Heavy-Duty, 20A, 120V, 12 AWG, 8.66-in. (21.99 cm), Black

MODEL NUMBER: P044-061





L5-20R to 5-20P heavy-duty power adapter transforms a NEMA 5-15/20R straight-blade outlet to a locking L5-20R outlet.

Features

Heavy-Duty Power Adapter Connects Devices That Require a Heavy-Gauge ConnectionThis heavy-duty adapter features 12 AWG wire suitable for high power connections, making it a reliable solution for large server applications that require a higher-rated, heavier-gauge cable. The six-inch power adapter transforms a NEMA 5-15/20R straight-blade outlet into a locking L5-20R outlet. It is also a recommended replacement or upgrade of a standard power cord provided by the device's manufacturer.

Locking L5-20R Connector Helps Prevent Accidental Disconnection and Expensive

DowntimeHaving a cable come loose accidentally can mean the loss of power and costly downtime. The locking NEMA L5-20R connector helps you avoid such danger, protecting critical equipment by maintaining a secure link without failure. The locking adapter is also invaluable when moving equipment in a rack or removing equipment from tight areas, ensuring the power cord always stays connected.

Highlights

- 8.66 in. adapter allows easy transition to L5-20R outlet with no electrician needed
- Heavy-duty cable replaces or upgrades standard power cord provided by manufacturer
- Thick 12 AWG wire gauge manages high power levels required for larger equipment
- Locking connector maintains secure link to avoid loss of power and costly downtime

Applications

- Transform a non-locking outlet into a locking outlet to prevent a power loss due to accidental disconnection
- Update or replace the standard power cord provided by a device's original manufacturer

Package Includes

 P044-06l L5-20R to 5-20P Heavy-Duty Power Adapter, 8.66 in., Black

Specifications

OVERVIEW		
UPC Code	037332139115	
Device Compatibility	Server; UPS; PDU	
Country/Region	North America	
INPUT		
Maximum Input Amps	20	
Voltage Compatibility (VAC)	125	



PHYSICAL		
Plug Color	Black	
Cable Jacket Color	Black	
Cable Jacket Material	PVC	
Cable Jacket Rating	VW-1	
Power Cord Jacket Type	SJT	
Cable Outer Diameter (OD)	11mm	
Number of Conductors	3	
Wire Gauge (AWG)	12	
Wire Gauge (OD - mm²)	3.31	
Cable Length (ft.)	0.72	
Cable Length (m)	0.22	
Cable Length (cm)	21.99	
Shipping Dimensions (hwd / cm)	25.40 x 17.78 x 0.25	
Shipping Dimensions (hwd / in.)	10.00 x 7.00 x 0.10	
Shipping Weight (kg)	0.18	
Shipping Weight (lbs.)	0.40	
ENVIRONMENTAL		
Operating Temperature Range	-4 F TO 140 F (-20 C TO 60 C)	
Storage Temperature Range	-4 F TO 140 F (-20 C TO 60 C)	
Operating Humidity Range	10 TO 65% RH	
Storage Humidity Range	10 TO 65% RH	
CONNECTIONS		
Side A - Connector 1	NEMA 5-20P	
Side B - Connector 1	NEMA L5-20R	
FEATURES & SPECIFICATIONS		
High Voltage	No	
Locking Plug	No	
Angled Plug	No	
STANDARDS & COMPLIANCE		
Product Certifications	cUL Listed; UL Listed	
Product Compliance	RoHS	



Tripp Lite1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234

WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies