

## AL62424C

### Linear Power Supply/Charger Kit

Altronix AL62424C linear power supply/charger kit has a wide range of applications including access control, security, and CCTV system accessories that require additional power. Kit includes: AL624 power supply, two (2) 12VDC/4AH rechargeable batteries, and 24VAC 40VA Class 2 Rated plug-in transformer.



AL62424C

### Specifications

#### Input

Voltage 115VAC, 60 Hz, 1.67A

#### Output

Voltage 24VDC  
 Current 0.75A supply current  
 Other Short circuit and thermal overload protection  
 Filtered and regulated

#### Back-up Battery *(not included)*

Type Sealed lead acid or gel type  
 Failover Upon AC loss, instantaneous

#### Indicators (LED)

Input Input voltage is present  
 DC Output Powered

### Physical and Environmental

#### Board Dimensions (L x W x H)

2.5" x 3" x 1.5" (63.5mm x 76.2mm x 38.1mm)

Product Weight 6.3 lbs. (2.76 kg)

Shipping Weight 7.1 lbs. (3.22 kg)

#### Temperature

Operating 0°C to 49°C (32°F to 120°F)

Storage -20°C to 70°C (-4°F to 158°F)

Relative Humidity 85% +/-5%

BTU/Hr. (approx.): 9 BTU/Hr.

Mounting hardware included.

#### Lifetime Warranty