



LED-2364HD

This LED-backlit monitor features the latest technology with enhanced picture clarity and sharpness which is ideal for broadcast production and video surveillance applications.

Benefits

- LED backlight: brighter picture using less power
- Full HD (1080i/p) with no downscaling
- Great picture quality with motion adaptive 3D De-interlace noise reduction
- RS-232 Control
- IR Remote Control

Specifications

Mount	VESA 100 x 100mm
HD Compatible	Yes
Anti Glare Coating	Yes
Case	Durable ABS Plastic
IR Remote Control	Yes
Native Aspect Ratio	16:9
Visible Screen Size (WH)	20.5" x 11.54" / 521.28 x 293.22mm
Resolution	1920 x 1080 (Full HD)
Brightness Rating	250 cd/m ² (Nit)
Contrast Ratio	3000:1
Back Light	LED
Color Depth	16.7 million
Number of Pixels	2,073,600
Response Time	5ms (Rising/Falling)
Audio Power / Speakers	2 Speakers x 2.5 Watts
Viewing Angle (L/R/T/B)	85/85/85/85 degrees
Digital Signal Processor	3D Comb Filter
Dimensions	22.6" x 14" x 1.8" / 573.3 x 355.2 x 46.7mm
Operating Temp	32 ~ 104°F / 0 ~ 40°C
Humidity	10% ~ 90%
Power Requirements	100 ~ 240 VAC, 50/60 Hz; 12VDC / 3.3A; AC adapter included
Power Consumption	<35 Watts (Active) / 0.5 Watts (Stand-by)
VGA	x1 Input
HDMI	x1 Input
Composite	x2 BNC Inputs / Outputs
RS-232	x1 Input
S-Video	x1 Input
Audio	x2 Inputs
Power	x1 DC12V Input
Weight	Net: 9.04 lbs / 4.1 kg; Gross: 12.57 lbs / 5.7 kg

Specifications subject to change.