

L-PJM20A

Unidirectional Projection Loudspeaker

- Intelligent voice and superior sound reproduction
- Ceiling or wall mount
- Meets virtually every indoor and outdoor requirement
- UL60065 and RoHS compliant



This loudspeaker is a high-performance, 20 W public address unidirectional projection loudspeaker. It offers a broad frequency response range, low distortion, and a high sound pressure level. This results in the accurate and intelligible broadcast of evacuation messages, and high-quality sound reproduction.

It can be used for indoor, outdoor, dry, or wet applications, providing reliable operation over a wide range of temperatures and humidity levels. Its low-profile, white color design blends easily with most interiors in hotels, conference rooms, cinemas, theme parks, factories, exhibitions, and more. The loudspeaker is both UL60065 and RoHS compliant.

WARRANTY

2 Years

Technical Specifications

Electrical

Max power	30 W
Rated power	20 W
Power tapping	20 W/10 W/5 W/2.5 W
Sound pressure level at 20 W/1 W (1m, 200 Hz~ 15 kHz)	102 dB/90 dB
Effective frequency response range (-10 dB)	150 Hz ~ 20 kHz
Dispersion angle (1 kHz/-6 dB)	180°
Rated input voltage	70 V
Rated impedance	245Ω/490Ω/980Ω/ 1960Ω
Connection	Fire-resistant cable

Mechanical

Dimensions	Ø140 mm x 195 mm
Weight	2.62 kg (5.78 lbs)
Color	RAL9003
Speaker size	5.25"

Environmental

Operating temperature	-25°C to + 55°C (-13°F to 131°F)
Storage temperature	-40°C to +70°C (-40°F to 158°F)
Relative humidity	<95%

Note: Honeywell reserves the right, without notification, to make changes in product design and/or specifications.

Honeywell Security and Fire

12 Clintonville Road
Northford, CT 06472, USA
Tel:+1.800.323.4576
www.honeywell.com