

DS-2CD7026G0**2 MP Indoor Network Box Camera****DarkFighter****DeepinView**^{series}

- 1/1.8" (2 MP) Progressive Scan CMOS
- 1080p Resolution @ 60 fps
- CS Lens Mount Options
- Auto-Iris, DC Drive
- H.265+, H.265, H.264+, H.264
- 140dB WDR
- MicroSD Card Slot Supports 256 GB
- 12 VDC and PoE (802.3af)

The Hikvision DS-2CD7026G0 Indoor Network Box Camera provides high definition output. It supports H.265+ video compression, which assures savings in bandwidth and storage. Darkfighter technology allows for viewing and recording in highly low-light conditions.

The camera can be equipped with up to eight different Hikvision lens options, which are installed on a standard CS mount.

Advanced DeepinView features, such as face detection and the ability to differentiate between specific target types, are supported.

Available models:
DS-2CD7026G0



Specifications

DS-2CD702660	
Camera	
Image Sensor	1/1.8" (2 MP) progressive scan CMOS
Minimum Illumination	Color: 0.002 lux @ (f/1.2, AGC on), B/W: 0.0002 lux @ (f/1.2, AGC on)
Shutter Speed	1s to 1/100,000 s
Slow Shutter	Yes
Auto-iris	DC drive
Day/Night	IR cut filter
Digital Noise Reduction	3D DNR
WDR	140 dB
Lens	
Lens Mount	CS Mount
Compression Standard	
Video Compression	Main stream:H.265+/H.265/H.264+/H.264; sub stream/third stream/fourth stream/fifth stream/custom stream: H.265+/H.265/H.264+/H.264/MJPEG
H.264 Type	Baseline profile/main profile/high profile
H.264+	Main stream supported
H.265 Type	Main profile
H.265+	Main stream supported
Video Bit Rate	32 Kbps to 16 Mbps
Smart-Feature Set	
Perimeter Protection	Line crossing, intrusion, region entrance, and region exiting. Supports alarm triggering by specified target types (human and vehicle). Filters out mistaken alarms caused by target types, such as leaves, lights, animals, flags, etc.
Event Detection	Unattended baggage detection, object removal detection, scene change detection, defocus detection, and audio exception detection
Face Detection and Capture	Face detection performance: up to 30 faces per frame. Face capture alarm frequency: up to 21 times per second. Detectable face position: left and right swings from -65° to 65°, up and down tilts from -45° to 45°.
Statistics	Counting
Region of Interest	Main stream/sub stream/third stream/fourth stream/fifth stream: four fixed regions and dynamic face tracking for each stream.
Image	
Maximum Resolution	1920 x 1080
Main Stream	60 fps [1920 × 1080, 1280 × 960, 1280 × 720]
Sub Stream	30 fps [704 × 480, 640 × 480]
Third Stream	30 fps [1920 × 1080, 1280 × 960, 1280 × 720, 704 × 480, 640 × 480]
Fourth Stream	30 fps [1920 × 1080, 1280 × 720, 704 × 480, 640 × 480]
Fifth Stream	30 fps [704 × 480, 640 × 480]
Custom Stream	30 fps [1920 × 1080, 1280 × 720, 704 × 480, 640 × 480]; up to 5 custom streams are supported
Image Enhancement	BLC, HLC, defog, 3D DNR, EIS
Image Setting	Rotate mode, saturation, brightness, contrast, sharpness, AGC, and white balance are adjustable by client software or web browser
Target Cropping	Yes
SVC	H.264 and H.265 encoding
Day/Night Switch	Day/night/auto/schedule/triggered by alarm in
Picture Overlay	Logo picture can be overlaid on video with a 128 × 128 24-bit bmp format
Network	
Network Storage	Supports microSD/SDHC/SDXC card (256 GB) local storage, NAS (NFS,SMB/CIFS), and ANR
Alarm Trigger	Motion detection, video tampering alarm, network disconnected, IP address conflict, illegal login, HDD full, HDD error
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, UDP, Bonjour
Security Measures	Password protection, HTTPS encryption, IEEE 802.1x port-based network access control, IP address filter, basic and digest authentication for HTTP/HTTPS, WSSE and digest authentication for ONVIF
General Function	One-key reset, anti-flicker, five streams and up to 5 custom streams, heartbeat, password protection, privacy mask, watermark, IP address filter
API	ONVIF (PROFILE S, PROFILE G), ISAPI, SDK
Simultaneous Live View	Up to 20 channels
User/Host	Up to 32 users. 3 user levels: administrator, operator and user
Client	iVMS-4200, Hik-Connect, Hik-Central
Web Browser	IE8+, Mozilla Firefox 30.0+, Google Chrome 31.0+, Safari 8.0+; plug-in free live view supported
Interface	
Communication Interface	One-port RJ45 10M/100M/1000M Ethernet port; one RS-485 interface (half duplex, HIKVISION, Pelco-P, Pelco-D, self-adaptive)
Alarm	Two inputs; two outputs (alarm output supports up to 24 VDC, 1 A or 110 VAC, 500 mA)
Video Output	One Vp-p composite output (75 Ω/CVBS)
Power Output	12 VDC, max. 200 mA
On-board storage	Built-in micro SD/SDHC/SDXC slot, up to 256 GB
BNC	CVBS analog output (4CIF resolution)
Reset Button	Yes
General	
Operating Conditions	-22° F to 140° F (-30° C to 60° C), humidity: 95% or less (non-condensation)
Power Supply	12 VDC ± 20%, 24 VAC± 20%, two-core terminal block; PoE (802.3af, class 4)
Power Consumption and Current	12 VDC, 0.8 A, maximum 9 W; 24 VAC, 0.4 A, maximum 9.5 W; PoE (802.3af, 36 V to 57 V), 0.1 A to 0.3 A
Material	Aluminum alloy
Dimensions	5.61" × 2.75" × 2.68" (142.6 mm × 69.8 mm × 68 mm)
Weight	Approximately 1.54 lbs (700 g)

Accessories

					
HV3816D-8MPIR Manual Focusing 8 MP IR Lens	HV1140D-8MPIR Manual Focusing 8 MP IR Lens	HV3816P-8MPIR Manual Focusing 8 MP IR Lens	HV0733D-6MP Manual Focusing 6 MP Lens	HF3417D-12MPIR Manual Focusing 12 MP IR Lens	HV0415D-MP Vari-Focal Auto Iris DC Drive 3 MP Lens

					
HV1250D-MPIR Manual Focusing 3 MP IR Lens	HV1140P-8MPIR Manual Focusing 8 MP IR Lens	DS-1331HZ Indoor Box Camera Housing	DS-1332HZ Outdoor Box Camera Housing	PP2 Pendant Mount	WBS Box Camera Wall Mounting Bracket

Dimensions

