

SLA-T4680D/T4680DW/T4680DS

2M Door Jamb Lens Modules



SLA-T4680D
(black)



SLA-T4680DW
(white)



SLA-T4680DS
(silver)

Key Features

- Compatible with XNB-6001
- Max. 2Megapixel (1920 x 1080) resolution
- 4.6mm pinhole lens
- 0.06Lux@F2.5
- 8m cable
- Easy installation
- Flexible panning ± 30 degrees
- Multiple housing color options to match the door jamb
- Hidden security screw for discrete look

| | SLA-T4680D | SLA-T4680DW | SLA-T4680DS | |
|----------------------------------|---|-----------------------------|-----------------|-----------------|
| VIDEO | | | | |
| Imaging Device | 1/2.8" 2M CMOS | | | |
| Total Pixels | 1,945(H) x 1,109(V) 2.16M | | | |
| Effective Pixels | 1,945(H) x 1,097(V) 2.13M | | | |
| Scanning System | Progressive Scan | | | |
| Min. Illumination | Color: 0.06Lux (F2.5) B/W: 0.06Lux (F2.5) | | | |
| S / N Ratio | 50dB | | | |
| Wide Dynamic Range | 120dB | | | |
| Day & Night | Electrical | | | |
| LENS | | | | |
| Focal Length (Zoom Ratio) | 4.6mm | | | |
| Max. Aperture | F2.5 | | | |
| Angular Field of | H: 73° / V: 39° / D: 85° | | | |
| Min. Object Distance | 0.98ft (0.3m) | | | |
| Lens Type | Fixed | | | |
| Mount Type | RJ12 connected with main unit | | | |
| ENVIRONMENTAL | | | | |
| Operating Temperature / Humidity | -10°C ~ +55°C (+14°F ~ +131°F) / Less than 90% RH | | | |
| Storage Temperature / Humidity | -50°C ~ +60°C (-58°F ~ +140°F) / Less than 90% RH | | | |
| MECHANICAL | | | | |
| Color / Material | Lens | Black / Plastic | Black / Plastic | Black / Plastic |
| | Cable | Black | Black | Black |
| | Housing | Black | White | Silver |
| Dimensions (WxHxD) | Lens | Ø0.94" x 1.65" (Ø24 x 42mm) | | |
| | Cable | 314.96" (8m) | | |
| Weight | 0.68 lb (310g) | | | |

* The latest product information / specification can be found at hanwha-security.com
 * Design and specifications are subject to change without notice.
 * Wisenet is the proprietary brand of Hanwha Techwin, formerly known as Samsung Techwin.

Dimensions

Unit: inch (mm)

