

## DS-2CD7526G0-IZHS/8

### 2 MP Outdoor Varifocal Network Dome Camera

## DarkFighter™



### LightFighter

### DeepinView<sup>series</sup>

- 1/1.8" (2 MP) Progressive Scan CMOS
- 1920 x 1080 Resolution @ 60 fps
- Human, Vehicle, and Face Detection
- EXIR 2.0 with up to 100 ft (30 m) and 165 ft (50 m) IR Range
- 2.8 to 12 mm and 8 to 32 mm Motorized Lenses
- Ultra-Low Light, 0.002 Lux (with f/1.2 Lens), Darkfighter Technology
- H.265+, H.265, H.264+, H.264
- 5 Defined Streams and 5 Custom Streams
- 140dB WDR, Lightfighter Technology
- Alarm Input/Output
- MicroSD Card Slot Supports 256 GB
- Convenient Integrated Conduit Base
- Anti-Fog Coating Inside of Lens Cover
- IP67, IK10 Protection
- 12 VDC and PoE (802.3af)

The Hikvision DS-2CD7526G0-IZHS/8 DeepinView Outdoor Varifocal Network Dome Camera includes deep learning technology for human, vehicle, and face detection. It supports H.265+ video compression, which assures savings in bandwidth and storage. Darkfighter technology allows for viewing and recording in ultra low-light conditions.

With a WDR of 140dB and Lightfighter technology, it provides superb image quality.

The camera is equipped with a 2.8 to 12 mm and 8 to 32 mm motorized varifocal lenses, and offers an EXIR 2.0 IR range of up to 100 ft (30 m) and 165 ft (50 m).

Smart features, such as line crossing, intrusion, scene change detection, and other event detection capabilities

#### Available models:

DS-2CD7526G0-IZHS





DS-2CD7526G0-IZHS8



# Specifications

DS-2CD752660-IZHS		DS-2CD752660-IZHS8	
<b>Camera</b>			
Image Sensor	1/1.8" Progressive Scan CMOS		
Minimum Illumination	Color: 0.002 lux @ (f/1.2, AGC on), 0 lux with IR		
Shutter Speed	1 s to 1/100,000 s		
Slow Shutter	Yes		
Day/Night	IR Cut Filter		
Digital Noise Reduction	3D DNR		
WDR	140dB		
Angle Adjustment	Bracket, pan: 0° to 355°, tilt: 0° to 90°, rotate: 0° to 360°		
<b>Lens</b>			
Focal Length	2.8 to 12 mm	8 to 32 mm	
Aperture	f/1.2	f/1.6	
Focus	Auto, semi-auto, manual		
FOV	Horizontal FOV 103.3° to 38.6°, vertical FOV 54.2° to 21.9°, diagonal FOV 124.2° to 44.3°	8 to 32 mm, horizontal FOV 42.5° to 13.4°, vertical FOV 23.4° to 7.7°, diagonal FOV 49° to 15.3°	
Lens Mount	Integrated		
<b>IR</b>			
IR Range	Up to 165 ft (50 m)	Up to 330 ft (100 m)	
Wavelength	850 nm		
<b>Compression Standard</b>			
Video Compression	Main stream: H.265+/H.265/H.264+/H.264; sub stream/third stream/fourth stream/fifth stream/custom stream: H.265+/H.265/H.264+/H.264/MJPE6		
H.264 Type	Baseline profile/main profile/high profile		
H.264+	Main stream support		
H.265 Type	Main Profile		
H.265+	Main stream support		
Video Bit Rate	32 Kbps to 16 Mbps		
Audio Compression	G.711/G.722.1/G.726/MP2L2/PCM		
Audio Bit Rate	64 Kbps (G.711)/16 Kbps (G.722.1)/16 Kbps (G.726)/32 to 192 Kbps (MP2L2)		
<b>Smart Features</b>			
Human and Vehicle Detection	Line crossing, intrusion, region entrance, region exiting; supports alarm triggering by specified target types (human and vehicle); Filtering out mistaken alarms caused by target types such as leaves, lights, animals, flags, etc.		
Event Detection	Unattended baggage, object removal, scene change, defocus, and audio exception detection		
Face Detection	Face detection performance: detects up to 30 faces at the same time. Face position: supports left and right swings from -65° to 65°, tilts up and down from -45° to 45°		
Statistics	Counting		
Region of Interest	Main stream/sub stream/third stream/fourth stream/fifth stream: four fixed regions and dynamic face tracking for each stream		
<b>Image</b>			
Maximum Resolution	1920 x 1080		
Main Stream	60 fps (1920 x 1080, 1280 x 960, 1280 x 720)		
Sub Stream	30 fps (704 x 480, 640 x 480)		
Third Stream	30 fps (1920 x 1080, 1280 x 960, 1280 x 720, 704 x 480, 640 x 480)		
Fourth Stream	30 fps (1920 x 1080, 1280 x 720, 704 x 480, 640 x 480)		
Fifth Stream	30 fps (704 x 480, 640 x 480)		
Custom Stream	30 fps (1920 x 1080, 1280 x 720, 704 x 480, 640 x 480); up to five custom streams are supported		
Image Enhancement	BLC, HLC, 3D DNR, Defog, EIS, lens distortion correction		
Image Setting	Rotate mode, saturation, brightness, contrast, sharpness, AGC, and white balance are adjustable by client software or web browser		
Target Cropping	Yes		
SVC	H.264 and H.265 encoding		
Day/Night Switching	Day/night/auto/schedule/triggered by alarm in		
Picture Overlay	Logo picture can be overlaid on video with 128 x 128 24 bit bmp format		
<b>Network</b>			
Network Storage	MicroSD/SDHC/SDXC card (256 GB), local storage and NAS (NFS,SMB/CIFS), ANR		
Alarm Trigger	Motion detection, video tampering alarm, network disconnected, IP address conflict, illegal login, HDD full, HDD error		
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, UDP, Bonjour		
Security Measures	Password protection, HTTPS encryption, IEEE 802.1x port-based network access control, IP address filtering, basic and digest authentication for HTTP/HTTPS, WSSE, and digest authentication for ONVIF		
General Function	One-key reset, anti-flicker, five streams and five custom streams, heartbeat, password protection, privacy mask, watermark, and IP address filtering		
API	ONVIF (PROFILE S, PROFILE G), ISAPI, SDK		
Simultaneous Live View	Up to 20 channels		
User/Host	Up to 32 users. 3 user levels: administrator, operator and user		
Client	iVMS-4200, Hik-Connect, Hik-Central		
Web Browser	Plug-in required for live view: IE 8-11, Chrome 41-44, Mozilla Firefox 30.0-51, Safari 8.0+		
	Plug-in free live view: Chrome 45+, Mozilla Firefox 52+		
<b>Interface</b>			
Audio	One-ch 3.5 mm input (line in), one-ch 3.5 mm output (line out), mono		
Communication Interface	One RJ45 10M/100M/1000M Ethernet port		
Alarm	One input, one output (up to 12 VDC 1A or 10 VAC 500 mA)		
Video Output	One Vp-p composite output (75 Ω/CVBS), 4CIF resolution		
Power Output	12 VDC, maximum 100 mA (supported by all power supply types)		
On-Board Storage	Built-in microSD/SDHC/SDXC slot, up to 256 GB		
Reset Button	Yes		
<b>Audio</b>			
Environment Noise Filtering	Yes		
Audio Sampling Rate	8 kHz/16 kHz/32 kHz/44.1 kHz/48 kHz		
<b>General</b>			
Operating Conditions	-40° F to 140° F (-40° C to 60° C); humidity 95% or less (non-condensing)		
Power Supply	12 VDC ± 20%, two-core terminal block; PoE (802.3at, class 4)		
Power Consumption and Current	12 VDC, 1.3 A, maximum 16 W; PoE (802.3at, 42.5 V to 57 V), 0.4 A to 0.3 A, class 4		
Protection Level	IP67, IK10		
Heater	Yes		
Material	Aluminum alloy		
Dimensions	Camera: Ø 6.4" x 5.5" (Ø 162 mm x 140.3 mm)		
Weight	Camera: 4.30 lbs (1.95 kg)		

# Accessories

			
<b>CPM + PC155</b> Ceiling Pendant Mount + 155 mm Pendant Cap	<b>WML + PC155</b> Wall Mount Long + 155 mm Pendant Cap	<b>PM</b> Pole Mount	<b>CM</b> Corner Mount

# Dimensions

