

Product data sheet

Specifications



Rack PDU Extender, Basic, 2U, 30A, 100/120/200/208V, (4)L5-30



AP7583

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Main Input Voltage	120 V 208 V
Main Output Voltage	120 V
Plug standard	NEMA L14-30P
Number of rack unit	2U
Cable length	8.53 m
Provided equipment	Installation guide Rack mounting brackets

Physical

Colour	Black
Height	8.9 cm
Width	43.7 cm
Depth	8.9 cm
Net weight	6.36 kg
Mounting location	Front Rear
Mounting preference	Lower
Mounting mode	Not rack-mountable

Input

[In] rated current	24 A
Input current limits	30 A
Load capacity	4992 VA
Network frequency	50/60 Hz

Output

Number of power socket outlets	4 NEMA L5-30R
--------------------------------	---------------

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Conformance

Product certifications	cUL listed METI Denan UL listed
Standards	CSA C22.2 No 107.1 UL 1778

Environmental

Ambient air temperature for operation	0...45 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...15240.00 m

Packing Units

Package 1 Weight	7.27 kg
Package 1 Height	15.2 cm
Package 1 width	52.1 cm
Package 1 Length	52.1 cm

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Compliant EU RoHS Declaration
Lead free	Yes
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------