**HDP Film Options:** 



## FARGO® HDP5000



<b>Print Method:</b>	HDP® Dye-Sublimation	/ Resin Thermal Transfer

Resolution: 300 dpi (11.8 dots/mm)

Colors: Up to 16.7 million / 256 shades per pixel

Full-color, YMC\*, 750 prints
Full-color with resin black, YMCK\*, 500 prints

**Print Ribbon Options:** 

Full-color with two resin black panels, YMCKK\*, 500 prints,
 Full-color with resin black and heat seal panel for difficult-to-print surfaces, YMCKH\*, 500 prints

 Full-color with resin black and inhibit panel for signature or other non-printing areas, YMCKI\*, 500 prints • Full-color with fluorescing and resin black, YMCFK\*,

500 prints • Resin black, K, 3000 prints

• Clear (1,500 prints) • Standard Holographic (500 prints) • Custom Holographic, special order (500 prints)

Thermal Transfer Overlaminate, .25 mil thick, 500 prints
 PolyGuard® Overlaminate, 1.0 mil and .6 mil thick, 250 prints (PolyGuard available in a CR-80 patch size)

**Overlaminate Options:** All overlaminates available in clear, standard holographic design or custom holographic design

Batch Mode:

Print Speed:\*\*

Batch Mode:

Up to 24 seconds per card / 150 cards per hour (YMC with transfer)\*

Up to 29 seconds per card / 124 cards per hour (YMCK with transfer)\*

Up to 40 seconds per card / 90 cards per hour (YMCK with transfer)\*

Up to 35 seconds per card / 102 cards per hour (YMCK with transfer and dual-sided, simultaneous lamination)\*

Up to 48 seconds per card / 75 cards per hour (YMCKK with transfer and dual-sided, simultaneous lamination)\*

**Accepted Standard Card Sizes:** CR-80 (3.370"L x 2.125"W / 85.6mmL x 54mmW)

> Over-the-edge on CR-80 cards **Print Area:**

 Print only: .030" (30 mil) to .050" (50 mil) / .762mm to 1.27mm
 Print/Lamination: .030" (30 mil) to .050" (50 mil) / .762mm to 1.27mm **Accepted Card Thickness:** ABS Laminated PVC PET PETG proximity smart and mag stripe cards

**Accepted Card Types:** Note: ABS and PVC cards are not recommended for use in the HDP5000 Lamination Module.\*\*\*

Input Card Cartridge Capacity: 100 cards (.030" / .762mm) Output Hopper Card Capacity: 200 cards (.030" / .762mm)

> Card Cleaning: Replaceable cleaning roller (included with each print ribbon)

Display:

**Software Drivers:** Windows® 10 / 8.1 / 8 / 7 / Vista® / XP / Server 2012 / Server 2012 R2 / Server 2008 / Server 2008 R2 / Server 2003

ISO Magnetic Stripe Encoding, dual high- and low-coercivity, Tracks 1, 2 and 3 Single Wire USB 2.0 Contactless Smart Card Encoder (HID iCLASS® and MIFARE)
 ISO 7816 Contact Smart Card Encoder

**Encoding Options:** Prox Card Reader (HID read-only)

USB 2.0 (high speed) and Ethernet with internal print server Interface:

**Operating Temperature:** 65° to 90° F / 18° to 32° C

**Humidity:** 20 - 80% non-condensing

• HDP5000: 11.50"H x 12.25"W x 9.25"D / 292mmH x 313mmW x 235mmD • HDP5000 + Dual-Sided Module: 11.50"H x 17.50"W x 9.25"D / 292mmH x 445mmW x 235mmD • HDP5000 + Single-Sided Lam Module: 12.75"H x 25"W x 9.25"D / 324mmH x 635mmW x 235mmD

**Dimensions:** HDP5000 + Dual-Sided Module + Dual-Sided Lam Module: 12.75"H x 30"W x 9.25"D / 324mmH x 762mmW x 235mmD
 Lam Module: 12.75"H x 12.25"W x 9.25"D / 324mmH x 313mmW x 235mmD

• HDP5000: 16 lbs. / 7.3 kg, HDP5000 + Dual-Sided Module: 22 lbs. / 10 kg, HDP5000 + Single-Sided Lam Module: 28 lbs. / 12.7 kg, HDP5000 + Dual-Sided Module + Dual-Sided Lam Module: 36 lbs. / 16.4 kg

UL, CE, IC, ECC Class-A, CCC, BSML KC, MIC Certifications:

**Supply Voltage:** 100-240 VAC, 3.3A

Supply Frequency: 50 Hz / 60 Hz

> • Printer - Three years\*\*\*\* including one year of free printer loaner support with option to purchase a second year of printer loaner support (U.S. only) Warrantv: • Printhead - Lifetime\*\*\*\*; unlimited card passes

FARGO Card Printer/Encoders require highly specialized media to function properly. To maximize printed card quality and durability, printhead life and

**FARGO Secure Materials:** printer/encoder reliability, use only HID Secure Materials HID warranties are void, where not prohibited by law, when non-HID Secure Materials are used.

• Dual card input hopper module • Card lamination module - single-sided or dual-sided (simultaneous)\*\*\* • Magnetic stripe encoding • 200-card input hopper • Smart card encoding (contact/contactless) • Dual-sided printing • Door and cartridge locks • Printer cleaning kit Options:

• Secure proprietary consumables system • Custom secure holographic HDP Film and overlaminate

Software: FARGO Workbench diagnostic utility with Color Assist spot-color matching \* Indicates the ribbon type and the number of ribbon panels printed where Y=Yellow, M=Magenta, C=Cyan, K=Resin Black, I=Inhibit, F=Fluorescing, H=Heat Seal

- \*\* Print speed indicates an approximate print speed and is measured from the time a card drops into the output hopper to the time the next card drops into the output hopper. Print speeds do not include encoding time or the time needed for the PC to process the image. Process time is dependent on the size of the file, the CPU, amount of RAM and the amount of available resources at the time of the print.
- ABS and PVC cards are not recommended for use in the HDP5000 Lamination Module. (Free card proofing available. Please contact your local integrator for more information.)
- \*\*\*\* Three-year warranty available on printers and lifetime warranty available on printheads with completion of online printer registration. (Two-year warranty standard on both printer and printheads without online printer registration.)



North America: +1 512 776 9000 Toll Free: 1800 237 7769

Europe, Middle East, Africa: +44 1440 714 850

Asia Pacific: +852 3160 9800 Latin America: +52 55 9171 1108 © 2020 HID Global Corporation/ASSA ABLOY AB. All rights reserved. HID, HID Global, the HID Blue Brick logo, the Chain Design, iCL ASS, HDP and FARSO are trademarks or registered trademarks of HID Global or its licensor(s)/supplier(s) in the US and other countries and may not be used without permission. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their





