

Product data sheet

Specifications



Rack PDU 2G, Switched, ZeroU, 20A, 100-120V, (24) 5-20R

AP8930

Overview

Presentation

APC Switched Rack Power Distribution Units (PDUs) enable advanced, user-customizable power control and active monitoring. Remote outlet level controls allow power on/off functionality for power recycling to remotely reboot equipment and restrict unauthorized use of individual outlets. Power sequencing delays allow users to define the order in which to power up or down attached equipment. Avoid circuit overload during power recovery and extend uptime of critical equipment by prioritizing the load shedding. Current metering provides real-time remote monitoring of connected loads. Switched Rack PDUs include real power monitoring, a temperature/humidity sensor port, locking IEC receptacles, and low profile circuit breakers. User-defined alarms warn of potential circuit overloads before critical IT failures occur. Users can access, configure, and control Switched Rack PDUs through secure Web, SNMP, or Telnet Interfaces and is complimented by APC Centralized Management platforms using InfraStruxure Central, Capacity Manager and Change Manager.

Lead time

Usually in Stock

Main

Main Input Voltage

120 V

Main Output Voltage

120 V

Plug standard

NEMA L5-20P

Number of rack unit

0U

Cable length

3.00 m

Number of cables

1

Provided equipment

Installation guide
Rack mounting brackets
Serial configuration cable
Safety guide

Physical

Colour

Black

Height

179.1 cm

Width

5.5 cm

Depth

4.6 cm

Net weight

6.52 kg

Mounting location

Side

Mounting preference

No preference

Mounting mode

Not rack-mountable

Input

[In] rated current

16 A

Permissible voltage	100...120 V
Input current limits	20 A
Load capacity	1920 VA
Network frequency	50/60 Hz

Output

Number of power socket outlets	24 NEMA 5-20R
--------------------------------	---------------

Conformance

Product certifications	cUL listed UL listed
Standards	FCC part 15 class A ICES-003 UL 60950-1

Environmental

Ambient air temperature for operation	-5...60 °C
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0.00...15240.00 m

Packing Units

Package 1 Weight	8.6 kg
Package 1 Height	200.6 cm
Package 1 width	16.47 cm
Package 1 Length	10.83 cm

Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Compliant EU RoHS Declaration
Lead free	Yes
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------