



LED-1906HDMTR

High-definition, LED-backlit, mid-size monitor with TV tuner that is versatile and effective for any commercial video use.

Benefits

- Displays HD signals (1080i/p and 720p)
- 3D + 3D image processing with digital noise reduction
- Built-in ATSC / Clear QAM digital tuner
- Built-in speakers
- IR remote control

Related Products

- LCD-1906HDTL: Flush mount version
- LCD-1906HDT: Wall mount version with removable desk stand

Specifications	
Mount	Rack: 7RU
Screen Panel	18.5" TFT Active Matrix
HD Compatible	Yes
Anti Glare Coating	Yes
V Chip/Closed Caption	Yes
Case	Durable Metal
IR Remote Control	Yes
Native Aspect Ratio	16:9
Visible Screen Size (WH)	16.1" x 9.1" / 409.8 x 230.4mm
Resolution	1366(H) x 768(V)
Brightness Rating	230 cd/m ² (Nit)
Contrast Ratio	1000:1
Back Light	LED
Dot Pitch	0.30(H) x 0.30(V)mm
Color Depth	16.7M
Number of Pixels	1,049,088
Response Time	5ms (Rising/Falling)
Audio Power / Speakers	8 Ohm, 2 Speakers x 2 Watts
Viewing Angle (L/R/T/B)	85/85/80/80 degrees
3D Comb Filter	Yes
Operating Temp/Humidity	6 ~ 104°F / -14 ~ 40°C
Power Requirements	100 ~ 240 VAC, 50/60 Hz
Power Consumption	<25 Watts; 0.5 Watts (Stand-by)
Component	x1 RCA YPbPr Input
Composite	x2 RCA Inputs; x1 RCA Output
VGA (RGB)	x1 15-pin mini D-sub Input
HDMI	x3 Inputs
TV (RF)	x1 F (Coax) Input
Audio	x1 RCA L/R Output; x1 3.5mm earphone Output
Weight	Net: 11.4 lbs / 5.2 kg; Gross: 13.4 lbs / 6.1 kg

Specifications subject to change.