

# WDL-1900M

## Color 19" TFT LCD Flat Screen Monitor

- High resolution 1280 x 1024
- Thin cross section - less than 2.5" deep panel
- 16.7million colors for true color rendition
- Multiple inputs - composite video, HDMI, D-sub
- Audio (left/right) line inputs and built-in speaker
- Audio outputs - speaker / earphone
- Contrast ratio of 1000:1
- Brightness of 250cd / m<sup>2</sup>
- Viewing angle - 160° (H) x 160° (V)
- On-screen menu display for feature and video adjustments
- Power supply included
- Includes wireless remote control and PC cable



## Specification

<b>Display type</b>	Active matrix color TFT LCD
<b>Screen size</b>	19" (diagonal)
<b>Viewable size (mm)</b>	376.32 x 301.056
<b>Viewable angle</b>	160° (H) x 160° (V)
<b>Pixel pitch (mm)</b>	0.294 (H) x 0.294 (V)
<b>Wall mounting</b>	Yes
<b>Brightness</b>	250cd/m <sup>2</sup>
<b>Resolution</b>	SXGA (1280 x 1024)
<b>Display color</b>	16.7M color
<b>Pixel format</b>	RGB vertical stripe
<b>Interface</b>	Analog
<b>Video output</b>	Analog RGB (0.7Vp-p), HDMI, BNC composite (0.7Vp-p)
<b>Contrast ratio</b>	1000:1
<b>AC/DC adaptor</b>	AC100 ~ 240, 60/50Hz, DC12V/4.58A
<b>Built-in speakers</b>	with speaker (2W x 2stereo)
<b>Plug &amp; play level</b>	VESA DDC 1/2B
<b>I/O connector</b>	DC power in (DC12V), VGA 15pin D-sub, audio L/R in & speaker out & speaker in video 1 BNC, HDMI, rear gear signal, BNC loop out, external source signal (option)
<b>System type</b>	NTSC/PAL/SECAM/auto
<b>Power requirement</b>	48W, saving mode: 5W
<b>Response time</b>	TR3 / TF10 (msec)
<b>Video source</b>	Composite, HDMI, VGA
<b>Weight</b>	4.8kg (gross weight)
<b>Size</b>	17.0" (W) x 9.0" (D) x 16.8" (H)

# System Wiring

